



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



General ordering data

Order No.	1676640000
Part designation	ZDUS
Version	Feed-through terminal, Shield feed-through terminal, Wemid, dark beige, Direct mounting
EAN	4008190462871
Qty.	20 pc(s).

Product notes

Product description	The shielding braid from the stripped control cables is soldered to the ZDUS or crimped on with 2.8 x 0.8 mm cable-lug sleeves. The ZDUS can be installed along side of the ZDU 2.5, ZDU 2.5/3 AN, ZDU 4, ZDU 6 and ZTR 2.5.
---------------------	--

Additional technical data

Colour of insulating material	dark beige
Connection direction	top
End plate required	Yes
Installation advice	Direct mounting
Insulating material	Wemid
No. of levels	1
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Crimping
UL 94 flammability rating of insulation material	V-0

Conductors for clamping (rated connection)

Type of connection	Shield feed-through terminal
Connection direction	top
Solid, min.	0.5 mm ²
Solid, max.	2.8 mm ²
Flexible, min.	0.5 mm ²
Flexible, max.	1.5 mm ²

Dimensions

Width	4.8 mm
Height of lowest version	33.5 mm
Length	83.5 mm

Approvals

Approvals institutes

**Classifications**

eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

Classifications

Similar products

Order No.	Part designation	Version
-----------	------------------	---------