



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




## HC-D 7-AMLD-24/GR-OD

Order No.: 1684994

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1684994>

HEAVYCON panel mounting base D7, with single locking latch, height 24 mm, straight, aluminum, with aluminum protective cover, for male inserts

Commercial data	
GTIN (EAN)	
sales group	D011
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 509 (PC-2009)

**Product notes**

WEEE/RoHS-compliant since:  
09/27/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>General data</b>	
Note	For contact inserts HC-D7, D8, A3, A4, B5, HS2-D7
Design	D7
Height	24 mm
Locking type	With single locking latch


Protective cover	Yes
Degree of protection	IP54 / IP65 with sealing screw
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Zinc die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Material lock	Steel, galvanized
Single locking latch material	Zinc-plated steel and passivated
Material, protective cover	Zinc
Length of the assembly cutout	21.5 mm
Width of the assembly cutout	21.5 mm

**Accessories**

Item	Designation	Description
<b>Assembly</b>		
1686229	HC-D 7-DS-IP65	Sealing screw, for IP65 protection

**Diagrams/Drawings**

Dimensioned drawing



**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;