



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





General ordering data

Order No.	1688110000
Part designation	ZTA 4
Version	Modular terminal, accessories, Test adapter
EAN	4008190855666
Qty.	25 pc(s).

Product notes

Product description	The clip-on test adapter ZTA is used as a single thin element and as a test adapter strip for measurements in electrical cabinets. Conductors with cross-sections from 0.5 mm ² to 1.5 mm ² can be connected. The test adapter simply clips onto the terminal and thus guarantees reliable contact with the live busbar.
---------------------	--

Additional technical data

Installation advice	Direct mounting
---------------------	-----------------

Conductors for clamping (rated connection)

Clamping range, min.	0.5 mm ²
Clamping range, max.	1.5 mm ²
Type of connection	Plug-in connection
Stripping length	10 mm
Solid, min.	0.5 mm
Solid, max.	1.5 mm
Flexible, min.	0.5 mm
Flexible, max.	1.5 mm
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm
Flexible with ferrule, max. (DIN 46228/1)	1.5 mm

Dimensions

Width	5.1 mm
Height of lowest version	69 mm
Length	31 mm

Dimensions

Rating data

Rated cross-section	1.5 mm ²
Rated current	11 A

Test adapter

Function	Test adapter
With snap-in pegs	Yes

Test adapter dimensions

Height with TS 35	69 mm
With snap-in pegs	Yes

Test adapter rated data

Rated voltage	250 V
---------------	-------

Approvals

Approvals institutes



Classifications

eClass 4.1	NK
eClass 5.0	NK
eClass 5.1	NK

Similar products

Order No.	Part designation	Version
-----------	------------------	---------