



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Specification Sheet

Part Number: 170-03134



Braided Sleeving, Split Wrap, .5" Dia, PET, Black, 1200 ft/bulk reel

|                     |                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 170-03134                                                                                                                                                                                                                                                                                                                                                                                        |
| Type                | BSPSW120LB                                                                                                                                                                                                                                                                                                                                                                                       |
| Color               | Black (BK)                                                                                                                                                                                                                                                                                                                                                                                       |
| Features & Benefits | <ul style="list-style-type: none"><li>• Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.</li><li>• Unique construction retains shape and rigidity throughout unrolling.</li><li>• Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.</li></ul> |
| Quantity Per        | reel                                                                                                                                                                                                                                                                                                                                                                                             |
| Product Description | <p>A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.</p>                             |

|                                |                                                                      |
|--------------------------------|----------------------------------------------------------------------|
| Short Description              | Braided Sleeving, Split Wrap, .5" Dia, PET, Black, 1200 ft/bulk reel |
| Global Part Name               | BSPSW120LB-PET-BK                                                    |
| Length L (Imperial)            | 1200.0                                                               |
| Length L (Metric)              | 365.8                                                                |
| Bundle Diameter Min (Imperial) | 0.1                                                                  |
| Bundle Diameter Min (Metric)   | 2.54                                                                 |
| Bundle Diameter Max (Imperial) | 0.5                                                                  |
| Bundle Diameter Max (Metric)   | 12.7                                                                 |
| Diameter D (imperial)          | 0.5                                                                  |
| Diameter D (metric)            | 12.7                                                                 |
| Nominal Diameter (Imperial)    | 1/2                                                                  |
| Nominal Diameter (Metric)      | 12.7                                                                 |
| Wall Thickness WT (Imperial)   | 0.025                                                                |
| Wall Thickness WT (Metric)     | 0.64                                                                 |
| Material                       | Polyester (PET)                                                      |

|                                |                                   |
|--------------------------------|-----------------------------------|
| Material Shortcut              | PET                               |
| Flammability                   | UL 94 V0                          |
| Halogen free                   | Yes                               |
| Operating Temperature (Metric) | -94°F to +257°F (-70°C to +120°C) |
| Reach Complaint(Article 33)    | Yes                               |
| ROHS Complaint                 | Yes                               |
| UL Recognized (US)             | Yes                               |
| UL Recognized (US and Canada)  | Yes                               |
| Package Quantity(Imperial)     | 1200                              |
| Package Quantity (Metric)      | 365.76                            |
| Customs Number                 | 3926909987                        |
| Weight (Metric)                | 5.4                               |
| Weight (Imperial)              | 12.0                              |