



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Specification Sheet

Part Number: 170-03180



Braided Sleeving, Expandable, Splice Free, .25" Dia, PET, Black, 1000 ft/bulk reel

Article Number	170-03180
Type	BSP140BSF
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Weave construction adjusts to twisting and flexing without creating wrinkles or bends.• Durable construction offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus.• Color options available to provide easy visual and safety identification of critical wiring components.• Expands to 150% of nominal diameter for fast, easy installation.
Quantity Per	reel
Product Description	General purpose expandable braided sleeving provides flexible abrasion protection for wire bundles and hoses.
Short Description	Braided Sleeving, Expandable, Splice Free, .25" Dia, PET, Black, 1000 ft/bulk reel

Global Part Name

BSP140BSF-PET-BK

Length L (Imperial)

1000.0

Bundle Diameter Min (Imperial)

0.125

Bundle Diameter Min (Metric)

3.2

Bundle Diameter Max (Imperial)

0.437

Bundle Diameter Max (Metric)

11.1

Diameter D (imperial)

0.437

Diameter D (metric)

10.9

Nominal Diameter (Imperial)

1/4

Nominal Diameter (Metric)

6.35

Material

Polyester (PET)

Material Shortcut

PET

Flammability

FAR 25 FMVSS 302 UL 94 V0

Halogen free

Yes

Operating Temperature (Metric)

-94°F to +248°F (-70°C to +125°C)

Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	304.80
Customs Number	3926909987