

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Specification Sheet

Part Number: 170-03198



Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, 2" Dia, AL/GF, Silver, 2/box

Article Number	170-03198
Туре	BSHTTSW2SB
Color	Silver (SR)
Features & Benefits	•A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion. •Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments. •Cuts with ordinary scissors for fast, easy application.
Quantity Per	box
Product Description	Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant

and easy installation and maintenance.

heat away from sensitive wires and cables. Wrap-around design allows for fast

Short Description	Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, 2" Dia, AL/GF, Silver, 2/box
Global Part Name	BSHTTSW2SB-GF-AL-ML
Length L (Imperial)	4.0
Length L (Metric)	1.22
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	1.95
Bundle Diameter Max (Metric)	49.5
Diameter D (imperial)	2.0
Diameter D (metric)	50.80
Nominal Diameter (Imperial)	2
Nominal Diameter (Metric)	50.8
Wall Thickness WT (Imperial)	0.042
Wall Thickness WT (Metric)	1.06
Material	Glass fiber with aluminium foil (GF-AL)

Material Shortcut	GF-AL
Flammability	Non-Flammable
Halogen free	Yes
Operating Temperature (Metric)	-76°F to +491°F (-60°C to +255°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	2
Package Quantity (Metric)	2
Customs Number	7019901000

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

^{© 2018} HellermannTyton. All rights reserved.