



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Specification Sheet

Part Number: 170-03205



Braided Sleeving, Heavy-Duty, 2" Dia, PA6, Black, 50 ft/reel

Article Number	170-03205
Type	BSHDWV
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Tightly woven fabric bundles and protects cables and hoses from sunlight and abrasion damage; also deflects high pressure hose ruptures.• Nylon material resists gasoline, salt and other chemicals.• Cut to size easily with regular scissors.
Quantity Per	box
Product Description	Sleeving made of a tightly woven nylon fabric, slides onto hoses, cables and components to protect them from abrasion and environmental elements, including UV damage. Also protects surrounding surfaces from damage.
Short Description	Braided Sleeving, Heavy-Duty, 2" Dia, PA6, Black, 50 ft/reel

Global Part Name

BSHDWV-PA6-BK

Length L (Imperial)

50.0

Length L (Metric)

15.24

Bundle Diameter Min (Imperial)

0.1

Bundle Diameter Min (Metric)

2.54

Bundle Diameter Max (Imperial)

2.0

Bundle Diameter Max (Metric)

50.8

Diameter D (imperial)

2.07

Diameter D (metric)

50.58

Nominal Diameter (Imperial)

2

Nominal Diameter (Metric)

50.8

Wall Thickness WT (Imperial)

.045

Wall Thickness WT (Metric)

1.14

Material

Polyamide 6 (PA6)

Material Shortcut

PA6

Flammability	Non-Flammable
Halogen free	Yes
Operating Temperature (Metric)	-49°F to +248°F (-45°C to +120°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	15.24
Customs Number	3926909987