



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!





Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Note:

Two heel straps are recommended for reliable grounding and ESD protection, providing ground when one foot is off the floor.

Operator is grounded when foot is in contact with grounded dissipative or conductive flooring.

Desco recommends the use of foot ground tester item No. 19252 or 19253.

For additional information on the use and maintenance of foot grounders please ask for Technical Bulletins TB-2020 and TB-2040.

Item 17250 is UL listed.

Description:

The 17250 and 17252 Foot Grounders provide a continuous ground path between an operator and a properly grounded ESD protected floor. These foot grounders are designed for use on standard shoes. They can be easily adjusted to fit the individual wearer. These foot grounders are made from non-marring three layer yellow reversible static dissipative rubber with a textured grain black conductive inner layer. This unit includes a blue tab with carbon suffused fibers and a hook and loop fastening system for quick and easy fastening and removal. Full elastic strap provides maximum "flexing" comfort. The 17252 is UL listed. The product has been tested to ESD STM 97.2 - Floor Materials and Footwear Voltage Measurement in Combination with a Person. It is a suitable ESD footwear component in Flooring - Footwear System when used as the primary grounding method (3.5×10^7 ohms per ESD STM 97.1 Floor Materials and Footwear-Resistance Measurement in Combination with a Person.)



Key:

- A. 0.060 inch thick non-marring, solid, three layer, rubber material. Three layers consist of a yellow dissipative outer layer with a textured grain, black conductive inner layer, and a yellow dissipative outer layer. Will not mar floors or shoes with black marks.
- B. Nylon, blue ribbon, with 8 conductive threads, reversible, may be positioned on either side of foot.
- C. 3/4 inch wide blue non-elastic hook material.
- D. 3/4 inch wide blue stretch loop material, for quick and easy attachment to foot.
- E. Patented* one megohm flat "flex" resistor (17252 only)

listed for safety and date coded.

Tab to cup resistance:

10E6 - 10E7 Ohms @ 100 volts

ITEM #	DESCRIPTION
17250	Foot Ground, Heel, no resistor, RTG: $10^6 - 10^7$ Ohms
17252	Foot Ground, Heel, 1 megohm resistor, $10^6 - 10^7$ Ohms



Made in America

Our UL listed foot grounders are rated at 250 VAC. It is not recommended to use them where exposure to line voltages above 250 VAC is possible. **Caution:** The foot grounder is for ESD control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment.

*U.S. Patent Number 5,786,977

FOOT GROUND, HEEL, 3-LAYER, NON-MARRING

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: www.desco.com
 PHONE (909) 627-8178 FAX (909) 627-7449
 DESCO EAST: 90 HUDSON RD, CANTON, MA 02021-1407
 PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER
17250

DATE:
8/07

