## mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## **HellermannTyton**

## **Specification Sheet**

Part Number: 173-62000



Electromagnetic Protection Braided Sleeving, Flame Retardant, 20 mm Dia, PET; TNCU, TCBK, 164ft/Reel

Article Number	173-62000
Туре	HEGEMIPV020
Color	Tin-coloured and Black (TCBK)
Features & Benefits	• The patented material mix of the HEGMIPV0 braided sleeving offer electromagnetic protection and secure cable bundling. • The special combination of tin-plated copper and PBTV0 yarn offers optimal inside and outside abrasion resistance. • In restricted space areas, HEGMIPV0 is easy to apply without any threads and breaks in the metal.
Quantity Per	metre
Product Description	HellermannTyton's patented Helagaine HEGEMIP braided sleeving offers electromagnetic protection on highly sensitive electronic applications. This material mix of braided sleeving is self-extinguishing, according to UL94 V0, and is particularly suitable for areas where fire protection is imperative.

Short Description	Electromagnetic Protection Braided Sleeving, Flame Retardant, 20 mm Dia,PET;TNCU, TCBK, 164ft/Reel
Global Part Name	HEGEMIPV020-PBT/TNCU-ML

Length L (Imperial)	164.0
Length L (Metric)	50.0
Bundle Diameter Min (Imperial)	0.71
Bundle Diameter Min (Metric)	18
Bundle Diameter Max (Imperial)	0.98
Bundle Diameter Max (Metric)	25
Diameter D (imperial)	0.79
Diameter D (metric)	20
Nominal Diameter (Imperial)	3/4
Nominal Diameter (Metric)	20

Material	Polyester (PBT) Tin-plated copper (SNCU)
Material Shortcut	PBT TNCU
Flammability	UL 94 V0 FMVSS 302

Halogen free	No
Operating Temperature (Metric)	-40°F to +302°F (-40°C to +150°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	164
Package Quantity (Metric)	50
Customs Number	5902100000
Content Unit(BMEcat)	metre
Weight (Imperial)	22.05

© 2018 HellermannTyton. All rights reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions