



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Crimp contact - IPCC 16- 4-MT - 1733385

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Single crimp pin contact for flexible cable with 4 mm² cross section.

Product Features

- Simply snap into the VC-AR... panel cutout and you're done!
- No need for panel mounting flange
- Simply snap into the VC-AR... panel cutout and you're done!
- No need for panel mounting frame
- Crimp contacts are released using a flat-bladed screwdriver

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	100 pc
Weight per Piece (excluding packing)	1.8 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Electrical characteristics

Rated current	32 A
Maximum load current	32 A

Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
---------------------------------	-------------------

Mechanical characteristics

Conductor cross section	4 mm ²
Stripping length of the individual wire	8 mm
Insertion/withdrawal cycles	>= 25

General

Series	VC-D
--------	------

Crimp contact - IPCC 16- 4-MT - 1733385

Technical data

General

Connection method	Crimp connection
-------------------	------------------

Material data

Contact surface material	silver-plated
--------------------------	---------------

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440204
eCl@ss 9.0	27440204

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC000796

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

EAC / EAC / EAC

Ex Approvals

Crimp contact - IPCC 16- 4-MT - 1733385

Approvals

Approvals submitted

Approval details

EAC

EAC

EAC
