



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**Cable glands
VG M40-EXE MS****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Brass cable glands for use in ATEX areas

General ordering data

Order No.	1737250000
Type	VG M40-EXE MS
Version	Cable gland, Brass, nickel-plated, External thread: M 40
GTIN (EAN)	4008190956721
Qty.	10 pc(s).

Cable glands VG M40-EXE MS

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Length	38 mm	Net weight	268.2 g
--------	-------	------------	---------

Approvals

Approval for cable gland	Ex e II, II 2 GD
--------------------------	------------------

General information

AF size 1	52 mm	Cable gland	metric
Clamping range, max.	33.5 mm	Clamping range, min.	24.5 mm
External thread	M 40	Length of thread	11 mm
Material	Brass, nickel-plated	O-Ring	NBR
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Pitch of thread	1.5	Protection degree with GWDR	IP 68 - 5 bar (30 min.)
Seal insert	CR	Sealing	NBR
Torque for cap nut, max.	135 Nm	Torque for cap nut, min.	135 Nm
Torque for connecting adapter, max.	27.5 Nm	Torque for connecting adapter, min.	27.5 Nm

Classifications

ETIM 2.0	EC000441	ETIM 3.0	EC000441
UNSPSC	30-21-18-01	eClass 4.1	27-14-12-11
eClass 5.1	27-14-91-11	eClass 6.2	27-14-91-11
eClass 7.1	27-14-91-11		

Approvals

Approvals



ROHS	Conform
------	---------