

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Cable glands ADAP EX 2 1/2NPT-M63

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





The range of cable glands is rounded off by a large number of accessories.

Adaptors serve as connection pieces between threaded holes and cable glands with differing thread sizes and types.

General ordering data

Order No.	<u>1738230000</u>	
Туре	ADAP EX 2 1/2NPT-M63	
Version	Adaptor, Brass, nickel-plated, 2 1/2" NPT, 2 1/2 NPT, metric, IP 54	
GTIN (EAN)	4008190958107	
Qty.	1 pc(s).	



Cable glands ADAP EX 2 1/2NPT-M63

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany Fon: +49 5231 14-0

Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

ROHS

Net weight	200 g		
Approvals			
Approval for cable gland	II 2 GD, Ex d IIC, Ex e II, Ex tD		
General information			
California d	4	Firebours of About and	0.4 /0!! NDT
Cable gland	metric	External thread	2 1/2" NPT
Material	Brass, nickel-plated	Operating temperature range, max.	100 °C
Operating temperature range, min.	-40 °C	Protection degree with GWDR	IP 68
Classifications			
ETIM 2.0	F0000444	LINCOC	20.21.10.01
ETIM 3.0	EC000441	UNSPSC	30-21-18-01
eClass 4.1	27-14-12-96	eClass 5.1	27-14-92-01
eClass 6.2	27-14-91-11	eClass 7.1	27-14-91-11

Conform