



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





#### General ordering data

Order No.	1746770000
Part designation	ZPE 10
Version	Earth terminal, 10 mm <sup>2</sup> , Tension clamp connection, Wemid, green/yellow, TS 35
EAN	4008190996734
Qty.	25 pc(s).

#### Product notes

Product description	Z-series standard ranges provide solutions for conductor cross-sections from 0.05 to 35 mm <sup>2</sup> .
---------------------	---

#### PT OKIECEEx/ATEX rating data

EU-type examination certificate	KEMA99ATEX5514U
Download, German	KEMA99ATEX5514U_d.pdf
Download English	KEMA99ATEX5514U_e.pdf
IECEX Certificate of Conformity	IECEXULD05.0009U
Download	IECEXULD05.0009U_e.pdf
ATEX conductor cross-section	10 mm <sup>2</sup>
IECEX conductor cross-section	10 mm <sup>2</sup>
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	Einsatztemperaturbereich siehe EG-Baumusterprüfbescheinigung/IECEX-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

#### Additional technical data

Colour of insulating material	green/yellow
Connection direction	top
End plate required	Yes
Explosion-tested version "Ex e"	Yes
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No

**Additional technical data**

No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Clamped
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	PE terminal

**CSA rating data**

Min. cross-section (CSA)	AWG 16
Max. cross-section (CSA)	AWG 6

**Conductors for clamping (additional connection)**

Flexible with ferrule, min. (DIN 46228 pt 1)	1.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	10 mm <sup>2</sup>

**Conductors for clamping (rated connection)**

Clamping range, min.	1.31 mm <sup>2</sup>
Clamping range, max.	16 mm <sup>2</sup>
Type of connection	Tension clamp connection
2nd type of connection	clamped
Connection direction	top
No. of connections	2
Stripping length	18 mm
Blade size	1.0 x 5.5 mm
Gauge to IEC 60947-1	A6
Solid, min.	1.5 mm <sup>2</sup>
Solid, max.	16 mm <sup>2</sup>
Stranded, min.	10 mm <sup>2</sup>
Stranded, max.	16 mm <sup>2</sup>
Flexible, min.	1.5 mm <sup>2</sup>
Flexible, max.	10 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	1.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	10 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	10 mm <sup>2</sup>
AWG conductor size, min.	AWG 16
AWG conductor size, max.	AWG 6
AWG conductor size, min.	1.31 mm <sup>2</sup>
AWG conductor size, max.	13.3 mm <sup>2</sup>

**Dimensions**

Width	10.1 mm
Height of lowest version	50.5 mm
Length	73.5 mm



#### Dimensions

TS 35 offset 39 mm

#### PE rating data

PEN function No  
 Pollution severity 3  
 Rated cross-section 10 mm<sup>2</sup>  
 Rated impulse withstand voltage to adjacent terminal 8 kV  
 Rated short-time current 1200 A (10 mm<sup>2</sup>)  
 Rated voltage for adjacent terminal 800 V  
 Standards IEC 60947-7-2

#### UL rating data

Min. cross-section (UL) AWG 16  
 Max. cross-section (UL) AWG 6

#### Approvals

Approvals institutes



#### Downloads

STEP 1746770000\_28145\_ZPE\_10\_STP.stp

#### Classifications

eClass 4.1 27-14-03-05  
 eClass 5.0 27-14-03-05  
 eClass 5.1 27-14-03-05

#### Similar products

Order No.	Part designation	Version
1767670000	ZPE 10/3AN	Earth terminal, 10 mm <sup>2</sup> , Tension clamp connection, Wemid, green/yellow, TS 35