



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



ARK-6320

Intel® Atom™ Dual Core D510/D525 with 6 COM and 8 USB Fanless Box PC



Features

- Built-in Intel® Atom™ Dual Core D510 1.66 GHz/D525 1.8GHz
- Comprehensive I/O: Dual GbE, 8 x USB, 6 x COM, 1 x VGA, and audio
- Mini PCIe expansion slot
- Accepts DC12 V input
- Anti-vibration design for 2.5" SATA HDD Bay to ensure maximum reliability
- Built-in mounting bracket supports wall and table-mounting, with optional VESA mounting bracket
- Supports SUSIAccess and Embedded Software APIs



SUSIAccess



LISTED
E180881

CE FCC




Specifications


		ARK-6320-6M01E	ARK-6320-6M02E
Processor System	CPU	Intel Atom Dual Core D510 1.66 GHz	Intel Atom Dual Core D525 1.8 GHz
	L2 Cache	1MB	1MB
	System Chipset	Intel ICH8-M	
	BIOS	AMI 16 Mbit SPI Flash	
Memory	Technology	Single Channel DDR2 667 MHz	Dual Channel DDR3 800 MHz
	Max. Capacity	2 GB	4 GB
	Socket	1 x 200-pin SO-DIMM	2 x 204-pin SO-DIMM
Graphics	Chipset	Embedded Gen 3.5 + GFX Core	
	VRAM	Optimized Shared Memory Architecture up to 224 MB system memory	
	Interface	VGA: Supports up to 2048 x 1536 @ 60 Hz	VGA: Supports up to 2048 x 1536 @ 60 Hz
		DVI-D: Supports up to 1600 x 1200	DVI-D: Supports up to 1600 x 1200
Dual Display	LVDS: Single channel 18-bit up to 1366 x 768 (optional)	LVDS: Single channel 18/24-bit up to 1366 x 768 (optional)	
	VGA+LVDS	VGA+DVI-D	
Ethernet	LAN1	10/100/1000 Mbps Intel 82567V GbE, support Wake On LAN	
	LAN2	10/100/1000 Mbps Intel 82583V GbE, support Wake On LAN	
Audio	Interfaces	Line-in, Line-out, Mic-in	
IO Interface	Serial Ports	5 x RS232, 1 x RS232/422/485	
	USB Interface	8 x USB ports, USB 2.0 Compliant	
	watchdog timer	Programmable, 1~255 sec/min	
Storage	HDD	Supports one SATA 2.5" HDD Bay (support 9.5mm height only)	
	SSD	Supports one internal CompactFlash socket for type I/II CompactFlash disk	
Expansion	miniPCIe	1 x miniPCIe	
Software Support	Microsoft Windows	Win 7, XP Professional, XP Embedded	
Power Requirement	Power Type	ATX	
	Power Input Voltage	12 V _{DC} , ± 10%	
	Minimum Power Input	DC 12V @ 3.75A	
	Power Adapter	AC-to-DC, 60W DC12V/5A (optional)	
Power Consumption	Typical	23 W (with Intel Atom D525 1.8 GHz)	
	Max.	37 W (with Intel Atom D525 1.8 GHz)	
Mechanical	Construction	Aluminum housing	
	Mounting	Desk/wall-mounting	
	Dimensions (W x H x D)	200 x 73 x 200 mm (7.9" x 2.9" x 7.9")	
	Weight	4.14 kg (8.8 lb)	
Environment	Operating Temperature	0 ~ 40° C with 2.5" HDD, 0.7m/sec air flow	
	Storage Temperature	- 40 ~ 85° C (-40 ~185° F)	
	Relative Humidity	10 ~ 85% @ 50° C, non-condensing	
	Vibration Loading During Operation	With 2.5-inch HDD: 0.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 Oct./min, 1 hr/axis	
	Shock During Operation	With 2.5-inch HDD: 20 G, IEC 60068-2-27, half sine, 11 ms duration	
	EMC	CE, FCC, CCC, BSMI	
	Safety Certifications	CCC, BSMI, UL	

Dimensions


Unit: mm (inch)



Front Panel External I/O Mechanical Layout/Drawing ARK-6320-6M01E



Rear Panel External I/O Mechanical Layout/Drawing ARK-6320-6M01E



Ordering Information

Part No.	CPU	L2 Cache	Memory	DVI-I	RS-232/422/485	RS-232	USB 2.0	MiniPCIe	DC input
ARK-6320-6M01E	Intel Atom D510 1.66 GHz	1 MB	1 DDR2	-	1	5	8	1	12V
ARK-6320-6M02E	Intel Atom D525 1.8 GHz	1 MB	2 DDR3	DVI-D	1	5	8	1	12V

Note: Memory, storage and operating system bundled by request.

Packing List

Part Number	Description
-	1 x ARK-6320 unit
-	1 x Driver/Utility CD/Manual
-	1 x Traditional Chinese user manual for CCC
-	1 x China RoHS sheet
1960014487T001	2 x Mounting bracket
1990005896S000	4 x Rubber foot pad
1939000410	4 x Screw for rubber foot pad
1930002235	4 x Screw for hard drive mounting
2000017557	1 x IO label sticker

Optional Accessories

External AC-to-DC Adapter and Accessories

Part Number	Description
1757003934	AC to DC adapter, DC12V/60W
2070010875	WES 2009 ENG for ARK-6320-6M01E
2070010897	WES 2009 MUI 24 for ARK-6320-6M01E
2070010707	WES7 ENG 32 bit for ARK-6320-6M01E
2070010896	WES 2009 ENG for ARK-6320-6M02E
2070010933	WES 2009 MUI 24 for ARK-6320-6M02E
2070010932	WES7 ENG 32 bit for ARK-6320-6M02E
AMK-V008E	VESA mounting plate for ARK-6320/6322