



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





#### General ordering data

Order No.	1766770000
Part designation	SAI-8-F 3P IDC PUR 10M
Version	Sensor-actuator passive distributor IDC, M12, Fixed cable version, 10.00 m, LED: Yes
EAN	4032248107469
Qty.	1 pc(s).

#### Dimensions

Length	152 mm
Height	25 mm
Width	60 mm

#### Technical data

Ambient temperature, max.	80 °C
Ambient temperature, min.	-20 °C
Behaviour in fire	V-0
Bus system	without
Conductor O.D., max.	5 mm
Conductor O.D., min.	3.5 mm
Contact carrier material	PBT UL 94 V0
Contact surface	tinned
Contact tube O-ring material	Viton
Contact tube diameter	M12
Core O.D., max.	1.6 mm
Core O.D., min.	1.2 mm
Current per signal	2 A
Electrical isolation available	No
Housing colour	grey, RAL 7032
Housing material	Pocan
Insulation resistance	1 MΩ
LED colour for I/O function	yellow
LED colour for indicating operation	green
LED initiator	Yes
Number of contact sockets	8

**Technical data**

Ordering data, title	SAI-4/6/8-F IDC
Pollution severity	2
Protection class	IP 67
Rated voltage	32 V DC
Sheathing stripping length	15 mm
Suitable for cable carriers	Yes
Test voltage	1 kVeff
Threaded sockets	CuZn, nickel-plated
Total current	9 A
Wiring diagram	
max. connection of equal cross-section	10
max. current-carrying capacity per slot	3 A
max. voltage	30 V DC
min. voltage	10 V
No. of poles	3
Version	complete module
Cable length	10 m

**Approvals**

Approvals institutes

**Classifications**

ETIM 2.0	NK
ETIM 3.0	EC001856
eClass 4.1	NK
eClass 5.0	NK
eClass 5.1	NK

**Similar products**

Order No.	Part designation	Version
1766730000	SAI-4-F 3P IDC PUR 10M	Sensor-actuator passive distributor IDC, M12, Fixed cable version, 10.00 m, LED: Yes
1766720000	SAI-4-F 3P IDC PUR 5M	Sensor-actuator passive distributor IDC, M12, Fixed cable version, 5.00 m, LED: Yes
1766750000	SAI-6-F 3P IDC PUR 10M	Sensor-actuator passive distributor IDC, M12, Fixed cable version, 10.00 m, LED: Yes
1766740000	SAI-6-F 3P IDC PUR 5M	Sensor-actuator passive distributor IDC, M12, Fixed cable version, 5.00 m, LED: Yes
1766760000	SAI-8-F 3P IDC PUR 5M	Sensor-actuator passive distributor IDC, M12, Fixed cable version, 5.00 m, LED: Yes