



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





General ordering data

| | |
|------------------|---|
| Order No. | 1766780000 |
| Part designation | SAI-4-M 4P IDC |
| Version | Sensor-actuator passive distributor IDC, M12, Hood version, LED: Yes |
| EAN | 4032248107315 |
| Qty. | 1 pc(s). |

Dimensions

| | |
|--------|---------|
| Length | 102 mm |
| Height | 41.5 mm |
| Width | 60 mm |

Technical data

| | |
|-------------------------------------|----------------------|
| Ambient temperature, max. | 90 °C |
| Ambient temperature, min. | -20 °C |
| Behaviour in fire | V-0 |
| Bus system | without |
| Clamping range, max. | 1.5 mm ² |
| Clamping range, min. | 0.08 mm ² |
| Connection type PE | Screw connection |
| Contact carrier material | PBT UL 94 V0 |
| Contact surface | tinned |
| Contact tube O-ring material | Viton |
| Contact tube diameter | M12 |
| Core O.D., max. | 1.6 mm |
| Core O.D., min. | 1.2 mm |
| Current per signal | 2 A |
| Electrical isolation available | Yes |
| Hood sealing material | Viton |
| Housing colour | grey, RAL 7032 |
| Housing material | Pocan |
| Insulation resistance | 1 MΩ |
| LED colour for I/O function | yellow |
| LED colour for indicating operation | green |

Technical data

| | |
|---|---------------------|
| LED initiator | Yes |
| Number of contact sockets | 4 |
| Ordering data, title | SAI-4/6/8-M IDC |
| Pollution severity | 2 |
| Protection class | IP 67 |
| Rated voltage | 32 V DC |
| Test voltage | 1 kVeff |
| Threaded sockets | CuZn, nickel-plated |
| Total current | 10 A |
| Wiring diagram | |
| max. connection of equal cross-section | 10 |
| max. current-carrying capacity per slot | 3 A |
| max. voltage | 30 V DC |
| min. voltage | 10 V |
| No. of poles | 4 |
| Version | complete module |

Approvals

Approvals institutes

**Classifications**

| | |
|------------|----------|
| ETIM 2.0 | NK |
| ETIM 3.0 | EC001856 |
| eClass 4.1 | NK |
| eClass 5.0 | NK |
| eClass 5.1 | NK |

Similar products

| Order No. | Part designation | Version |
|------------|-------------------|--|
| 1766781000 | SAI-4-M 4P IDC UT | Sensor-actuator passive distributor IDC, M12, Hood version, LED: Yes |
| 1766790000 | SAI-6-M 4P IDC | Sensor-actuator passive distributor IDC, M12, Hood version, LED: Yes |
| 1766791000 | SAI-6-M 4P IDC UT | Sensor-actuator passive distributor IDC, M12, Hood version, LED: Yes |
| 1766800000 | SAI-8-M 4P IDC | Sensor-actuator passive distributor IDC, M12, Hood version, LED: Yes |
| 1804540000 | SAI-8-M 4P IDC PE | Sensor-actuator passive distributor IDC, M12, Hood version, LED: Yes |
| 1766801000 | SAI-8-M 4P IDC UT | Sensor-actuator passive distributor IDC, M12, Hood version, LED: Yes |