

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









## HC-B 6-KML-73/M1PG13,5G

Order No.: 1771192



http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1771192

Coupling housing, with single locking latch, height 73 mm, with screw connection, 1x Pg13.5

Commercial data	
GTIN (EAN)	4 017918 035938
sales group	D002
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 481 (PC-2009)

#### Product notes

WEEE/RoHS-compliant since: 03/01/2006



## http://

www.download.phoenixcontact.com Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## **Technical data**

#### General data

Note	For contact inserts HC-B6, BB10, DD24, M
Design	B6
Height	73 mm
Width	43 mm
Length	73 mm

Housing type	Coupling housings
Locking type	With single locking latch
Type of the screw connection	1x Pg13,5
Pg screw connection	With
Wrench size, union nut	20 mm
External cable diameter	7.5 mm 12.5 mm
Degree of protection	IP65
Ambient temperature (operation)	-40 °C 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Cable gland material	Nickel-plated brass
Cable seal material	NBR
Material lock	High-grade steel, handle: PA-GF
Material grip body interlock	PA-GF


## **Certificates / Approvals**




Certification GOST

## Diagrams/Drawings

## Dimensioned drawing





#### Address

PHOENIX CONTACT Deutschland GmbH Flachsmarktstr. 8 32825 Blomberg,Germany Phone +49 5235 3 12000 Fax +49 5235 3 41200 http://www.phoenixcontact.de



© 2010 Phoenix Contact Technical modifications reserved;