



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**Cable glands**  
**VG M50 - MS 68**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Screwed joints that comply with the high demands of class of protection IP 68

**General ordering data**

Order No.	<a href="#">1772260000</a>
Type	VG M50 - MS 68
Version	Cable gland, Brass, nickel-plated, External thread: M 50
GTIN (EAN)	4032248129911
Qty.	15 pc(s).

**Cable glands  
VG M50 - MS 68**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Length	57 mm	Net weight	280.2 g
--------	-------	------------	---------

**General information**

AF size 1	50 mm	AF size 2	55 mm
Clamp insert	Polyamide	Clamping range, max.	32 mm
Clamping range, min.	22 mm	External thread	M 50
Length of thread	9 mm	Material	Brass, nickel-plated
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Pitch of thread	1.5	Protection degree with GWDR	IP 68 - 5 bar
Torque for cap nut, max.	41.5 Nm	Torque for cap nut, min.	38.5 Nm
Torque for connecting adapter, max.	20 Nm	Torque for connecting adapter, min.	16 Nm

**Classifications**

ETIM 3.0	EC000441	eClass 6.2	27-14-91-09
eClass 7.1	27-14-91-09		

**Approvals**

Approvals



ROHS	Conform
------	---------