



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Data sheet

Order No.: 1777798

Type: FRONT-MSTB 2,5/ 8-STF-5,08

Plug component, Front screw connection



The figure shows a 10-position version of the product

1 Main features



- | | | | |
|---------------------------|------------------------|------------------------|---------------------|
| • No. of pos. | 8 | • Nominal current | 12 A |
| • Conductor cross section | 2.5 mm ² | • Nominal voltage | 320 V |
| • Color | green | • Connection direction | 0 ° |
| • Pitch | 5.08 mm | • Type of packaging | packed in cardboard |
| • Connection method | Front screw connection | | |

2 Your advantages

Well-known connection principle allows worldwide use

Optimized for tight installation situations: operation and conductor connection from one direction

Screwable flange for superior mechanical stability

Low temperature rise, thanks to maximum contact force

Allows connection of two conductors



Make sure you always use the latest documentation.


It can be downloaded at: phoenixcontact.net/product/1777798

1777798 FRONT-MSTB 2,5/ 8-STF-5,08**3 Table of contents**

1	Main features.....	1
2	Your advantages	1
3	Table of contents	2
4	3D model in PDF can be activated (Acrobat Reader only).....	3
5	item properties.....	4
	5.1 Connection capacity	4
	5.2 Specifications for ferrules	4
	5.3 Material data	4
6	4
7	Dimensions.....	4
	7.1 Dimensions for the product	4
8	Series drawing.....	5
9	Packaging information	5
10	Application.....	5
	10.1 Temperature limit values	5
11	Mechanical tests.....	6
12	6
	12.1 Termination and connection method.....	6
	12.2 Pull-out test	6
13	Electrical tests	7
	13.1 Electrical data	7
	13.2 Air and creepage distances	7
14	Current carrying capacity/derating curves	8
15	8
16	Environmental and durability tests	9
	16.1 Vibration test	9
17	Classification for connectors.....	9
18	Approvals	9
19	9
20	9
21	9
22	9
23	9
24	9

1777798 FRONT-MSTB 2,5/ 8-STF-5,08

4 3D model in PDF can be activated (Acrobat Reader only)



1777798 FRONT-MSTB 2,5/ 8-STF-5,08

5 [Redacted]

5.1 [Redacted]

5.2 [Redacted]

5.3 [Redacted]
Material of metal parts

6 [Redacted] Insulating material data [Redacted] Housing [Redacted]

7 Dimensions

7.1 [Redacted]

1777798 FRONT-MSTB 2,5/ 8-STF-5,08

8 Series drawing

9 Distribution drawing

10 Application

10.1 Temperature limit values

1777798 FRONT-MSTB 2,5/ 8-STF-5,08

11 Mechanical tests

11.1 Mechanical test group A

11.1.1 Termination and connection method

11.1.1.1 Pull-out test
Termination and connection method: pull-out test


13 Electrical tests

13.1 Electrical data



13.2 Air and pressure distances





18
/derating curves

Type: FRONT-MSTB 2,5/...-STF-5,08 with MDSTB 2,5/...-GF-5,08

Type: FRONT-MSTB 2,5/...-STF-5,08 with MDSTBV 2,5/...-GF-5,08

93029_1000_en

Type: FRONT-MSTB 2,5/...-STF-5,08 with CC 2,5/...-GF-5,08 P26THR

93060_1000_en

Type: FRONT-MSTB 2,5/...-STF-5,08 with MSTB 2,5/...-GF-5,08

Type: FRONT-MSTB 2,5/...-STF-5,08 with CCV 2,5/...-GF-5,08 P26THR



16 Environmental and durability tests

16.1 Vibration test

Specification	IEC 60068-2-6:2007-12
---------------	-----------------------

16.2 Climatic test

Specification	IEC 61984:2008-10
---------------	-------------------

18 Approvals

CSA

VDE Gutachten mit Fertigungsüberwachung

IECEE CB Scheme

cULus Recognized

EAC

DNV GL

1777798 FRONT-MSTB 2,5/ 8-STF-5,08

25 Commercial Data

Order No.	1777798
-----------	---------

Order No.	Type
-----------	------

Description	Order No.	Type
-------------	-----------	------

1777798 FRONT-MSTB 2,5/ 8-STF-5,08

29 Combination tests

FRONT-MSTB 2,5/...-STF	MDSTB 2,5/...-GF	MDSTBV 2,5/...-GF	CC 2,5/...-GF	MSTB 2,5/...-GF
Specification	IEC 61984	IEC 61984	IEC 61984	IEC 61984
Mechanical tests (A)				
Insertion/withdrawal force per position	approx. 12 N / 9 N	approx. 8 N / 6 N	approx. 8 N / 6 N	approx. 8 N / 6 N
Polarization when inserted Requirement >20 N	Test passed	Test passed	Test passed	Test passed
Contact holder in insert Requirements >20 N	Test passed	Test passed	Test passed	Test passed
Durability tests (B)				
Contact resistance R ₁	1.9 mΩ	2.6 mΩ	1.4 mΩ	1.4 mΩ
Insertion/withdrawal cycles	25	25	25	25
Contact resistance R ₂	1.9 mΩ	2.6 mΩ	1.4 mΩ	1.4 mΩ
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 μs)	4.8 kV	4.8 kV	4.8 kV	4.8 kV
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	2.21 kV	2.21 kV	2.21 kV	2.21 kV
Insulation resistance Requirements > 5 MΩ	> 0.2 TΩ	> 0.2 TΩ	> 0.2 TΩ	> 0.2 TΩ
Thermal tests (C)				
Tested number of positions	17	18	12	24
Tested conductor cross section	2.5 mm ²	2.5 mm ²	2.5 mm ²	2.5 mm ²
Test current	10 A	10 A	12 A	12 A
Upper limiting temperature Requirements < 100°C	Test passed	Test passed	Test passed	Test passed
Climatic tests (D)				
Test sequence 1: low temperature storage	-40 °C/2 h	-40 °C/2 h	-40 °C/2 h	-40 °C/2 h
Test sequence 2: heat storage	100 °C/168 h	100 °C/168 h	100 °C/168 h	100 °C/168 h
Test sequence 3: noxious gas storage (ISO 6988)	0.2 dm ³ SO ₂ on 300 dm ³ / 40 °C/1 cycle	0.2 dm ³ SO ₂ on 300 dm ³ / 40 °C/1 cycle	0.2 dm ³ SO ₂ on 300 dm ³ / 40 °C/1 cycle	0.2 dm ³ SO ₂ on 300 dm ³ / 40 °C/1 cycle
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 μs)	4.8 kV	4.8 kV	4.8 kV	4.8 kV
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	2.21 kV	2.21 kV	2.21 kV	2.21 kV
Environmental and endurance tests (E)				
Specification	IEC 61984:2008-10	IEC 61984:2008-10	IEC 61984:2008-10	IEC 61984:2008-10
Degree of protection	Finger safety with IP20 test finger	Finger safety with IP20 test finger	Finger safety with IP20 test finger	Finger safety with IP20 test finger

1777798 FRONT-MSTB 2,5/ 8-STF-5,08**FRONT-MSTB 2,5/..-STF****CCV 2,5/..-GF**

Specification

IEC 61984

Mechanical tests (A)

Insertion/withdrawal force per position

approx. 8 N / 6 N

Polarization when inserted
Requirement >20 N

Test passed

Contact holder in insert
Requirements >20 N

Test passed

Durability tests (B)Contact resistance R_1 1.3 m Ω

Insertion/withdrawal cycles

25

Contact resistance R_2 1.4 m Ω Rated impulse voltage at sea level
Voltage waveform \geq (1.2/50 μ s)

4.8 kV

Power-frequency withstand voltage
Voltage waveform \geq (50/60 Hz)

2.21 kV

Insulation resistance
Requirements > 5 M Ω > 0.1 T Ω **Thermal tests (C)**

Tested number of positions

12

Tested conductor cross section

2.5 mm²

Test current

12 A

Upper limiting temperature
Requirements < 100°C

Test passed

Climatic tests (D)

Test sequence 1: low temperature storage

-40 °C/2 h

Test sequence 2: heat storage

100 °C/168 h

Test sequence 3: noxious gas storage
(ISO 6988)0.2 dm³ SO₂ on 300 dm³/
40 °C/1 cycleRated impulse voltage at sea level
Voltage waveform \geq (1.2/50 μ s)

4.8 kV

Power-frequency withstand voltage
Voltage waveform \geq (50/60 Hz)

2.21 kV

Environmental and endurance tests (E)

Specification

IEC 61984:2008-10

Degree of protection

Finger safety with IP20
test finger