

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Incandescent Indicators

TWO TERMINALS— FULLY INSULATED
FOR MOUNTING IN 15/32" CLEARANCE HOLE

MEET OR EXCEED ENVIRONMENTAL AND OPERATIONAL REQUIREMENTS
OF MIL-L-6723 AND MIL-L -3661B.

MATERIALS AND FINISHES

- Mounting Bushing: Aluminum, black anodize finish.
- Internal-tooth Lockwasher and Mounting Nut: Steel, cadmium plated with yellow iridescent chromate finish.
- Terminals: Brass, hot tinned with elongated slot.

Feature

 Anti-rotation (locked) construction: Provides for secure locking of the socket terminal assembly in the mounting bushing and of the center terminal to the insulating disc. The notched mounting bushing receives the matched insulating disc to prevent the rotation of the mounting bushing.

> Per MIL-L-3661B QPL Listed



360-8430-0371-502 LH73/1; LC11RT2 Flat Lens

360 SERIES Colored Legends

Colored legends on black or gray lenses: Legends can also be furnished in "negative" or "reverse" style, in which the legend is illuminated in white or other color while the backround remains opaque black or gray. To obtain opaque black lens change the "03" in the part number to "57", and to "58" to obtain opaque gray lens.

Examples: 178-5871-500 (gray lens cap)

360-8430-5871-502 (complete assembly).

FRONT MOUNTING .018 ± .005 X 19/32 ± .020 O.D. INTERNAL TOOTH LOCKWASHER .3/32 X 9/16 ACROSS HEX. NUT .15/32–32 NS THD. MOUNTING BUSHING .055 .059 TERMINAL CONNECTED TO THE CENTER CONTACT. .034 ± .002 FLANGE Max. panel thickness 3/16" Recommended Panel Cutout

(1 1172/4) 250 0420 00 50

BASE PART NUMBERS

			7	(LH73/1/ 359-6430-09-502
CAP PART NUMBERS	TYPE DESIG.	PART NUMBER	LENS CAP COLOR	COMPLETE ASSEMBLY PART NUMBERS
	Flat—Non-Diffusing			;
5/16-32 NEF ·2 THD. 9/16 3/4 MAX. For legends on flat faced lens, see page P	LC11GN2 LC11YN2 LC11BN2	178-0333-500	Red Green Yellow (amber) Blue Clear (colorless)	360-8430-0331-502 360-8430-0332-502 360-8430-0333-502 360-8430-0334-502 360-8430-0337-502
	Flat-Trans LC11RT2 LC11GT2 LC11YT2 LC11BT2 LC11WT2	178-0371-500 178-0372-500 178-0373-500 178-0374-500 178-0375-500	Red Green Yellow (amber) Blue White	360-8430-0371-502 360-8430-0372-502 360-8430-0373-502 360-8430-0374-502 360-8430-0375-502

Part numbers shown in gray are normally in inventory at your Dialight Distributor.

Order complete with lamp to be assured of receiving the indicator light and correct lamp together for immediate use.