



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





General ordering data

Order No.	1780850000
Part designation	WF 6
Version	Stud terminal, 35 mm ² , Threaded stud connection, Wemid, dark beige, TS 35
EAN	4032248219339
Qty.	25 pc(s).

Product notes

Function	The pitch, related to the terminal carrier width with WTW, is 18 mm.
Note, accessories	With WTW...2300 made from epoxy resin, rated current is 2300 V according to prelim. EN 50124-1

Additional technical data

Colour of insulating material	dark beige
Connection direction	on side
End plate required	No
Explosion-tested version "Ex e"	No
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	1
Open sides	Open
Operating temperature range	- 50 °C, + 120 °C
Product family	W-Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	Stud terminal

CSA rating data

Voltage (CSA)	1,000 V
---------------	---------

CSA rating data

CSA current	150 A
Min. cross-section (CSA)	AWG 14
Max. cross-section (CSA)	AWG 2

Conductors for clamping (rated connection)

Type of connection	Threaded stud connection
Connection direction	on side
Flexible, min.	2.5 mm ²
Flexible, max.	35 mm ²

Dimensions

Width	17.8 mm
Height of lowest version	56 mm
Length	67 mm
TS 35 offset	31.5 mm

Rating data

Rated cross-section	35 mm ²
Rated voltage	1,000 V
Rated impulse voltage	8 kV
Rated current	125 A
Current with max. conductor	125 A
Pollution severity	3

Stud connection

2 cable lugs to DIN 46234	2.5...35 mm ²
2 cable lugs to DIN 46234	6...25 mm ²
Cable lug to DIN 46234	2.5...35 mm ²
Cable lug to DIN 46234	6...35 mm ²
Clamping range, max.	35 mm ²
Clamping range, min.	2.5 mm ²
Impulse voltage with epoxy resin partition plate	12 kV
Stud size for spade connection	M 6
Tightening torque range	3.0...6.0 Nm
Voltage with epoxy resin partition plate	2,300 V

UL rating data

Voltage (UL)	1,000 V
Current (UL)	115 A
Min. cross-section (UL)	AWG 14
Max. cross-section (UL)	AWG 2

Approvals

Approvals institutes



Approvals**Downloads**

STEP 1780850000_31394_WF_6_STP.stp

Classifications

ETIM 2.0	NK
ETIM 3.0	EC002020
eClass 4.1	NK
eClass 5.0	NK
eClass 5.1	NK

Similar products

Order No.	Part designation	Version
1790130000	WF 5	Stud terminal, 16 mm ² , Threaded stud connection, dark beige, TS 35
1780860000	WF 8	Stud terminal, 50 mm ² , Threaded stud connection, Wemid, dark beige, TS 35
1780870000	WF 10	Stud terminal, 120 mm ² , Threaded stud connection, Wemid, dark beige, TS 35
1780880000	WF 12	Stud terminal, 120 mm ² , Threaded stud connection, Wemid, dark beige, TS 35
1968990000	WF 5 NFF	
1969000000	WF 6 NFF	
1968960000	WF 8 NFF	
1968950000	WF 10 NFF	
1968940000	WF 12 NFF	