



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PLUGSERIES
ZQV 2.5N 1/4-2 BL

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



High power/currents can be safely switched with the PLUGSERIES. The modular system enables conventional relays and LED indicators simply to be plugged in. Retaining and disassembly clips provide a secure mount. Pre-assembled relays with 1 or 2 changeover contacts and input voltages from 24V to 230V round of the product range. Plug-in ZQV 2.5 cross-connectors enable relay multiplexers to be set up quickly thanks to simple side-by-side mounting.

General ordering data

Order No.	1784290000
Type	ZQV 2.5N 1/4-2 BL
Version	PLUGSERIES, Relays
GTIN (EAN)	4032248216383
Qty.	60 pc(s).

PLUGSERIES
ZQV 2.5N 1/4-2 BL

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	15 mm	Height	10 mm
Depth	31.5 mm	Net weight	1.733 g

Temperatures

Operating temperature	-40 °C...+50 °C	Ambient temperature	-40 °C...+50 °C
Storage temperature			

general data

UL 94 flammability rating	V-0	Ambient temperature	-40 °C...+50 °C
---------------------------	-----	---------------------	-----------------

Insulation coordination

Protection degree	IP 20
-------------------	-------

Other technical data

Version	Relay accessory - cross-connector
---------	-----------------------------------

Connection data

Pitch in mm (P)	5.1 mm
-----------------	--------

Classifications

ETIM 2.0	EC000489	ETIM 3.0	EC000489
UNSPSC	30-21-18-01	eClass 4.1	27-14-11-99
eClass 5.1	27-14-11-40	eClass 6.2	27-14-11-40
eClass 7.1	27-14-11-40		

Approvals

Approvals



ROHS	Conform
------	---------