



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# PCB terminal block - FFKDSA1/V-2.54-6 - 1789579

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



PCB terminal block, Nominal current: 6 A, Nom. voltage: 160 V, Pitch: 2.54 mm, Number of positions: 6, Connection method: Spring-cage conn., Mounting: Soldering, Conductor/PCB connection direction: 90 °

The illustration shows the 10-position version

## Key commercial data

Packing unit	1
Minimum order quantity	1
GTIN	 4 017918 330309
Custom tariff number	85369010
Country of origin	GERMANY

## Technical data

### Dimensions / positions

Length	12.6 mm
Pitch	2.54 mm
Dimension a	12.7 mm
Number of positions	6
Pin dimensions	0,5 x 0,8 mm
Hole diameter	1.1 mm

### Technical data

Range of articles	FFKDS(A)/V
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/3)	63 V
Rated voltage (III/2)	160 V
Rated voltage (II/2)	320 V
Connection in acc. with standard	EN-VDE
Nominal current I <sub>N</sub>	6 A
Nominal cross section	0.5 mm <sup>2</sup>
Stripping length	11 mm
Nominal voltage, UL/CUL Use Group B	150 V

# PCB terminal block - FFKDSA1/V-2.54-6 - 1789579

## Technical data

### Technical data

Nominal current, UL/CUL Use Group B	6 A
-------------------------------------	-----

### Connection data

Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	20
Minimum AWG according to UL/CUL	26
Maximum AWG according to UL/CUL	20

## Classifications

### eclass

eCl@ss 4.0	27141109
eCl@ss 4.1	27141109
eCl@ss 5.0	27141190
eCl@ss 5.1	27141190
eCl@ss 6.0	27261101
eCl@ss 7.0	27440401

### etim

ETIM 3.0	EC001121
ETIM 4.0	EC002643
ETIM 5.0	EC002643

### unspsc

UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432
UNSPSC 13.2	39121432

## Approvals

### Approvals

---

Approvals

CSA / UL Recognized / cUL Recognized / cULus Recognized

---

Ex Approvals

---

Approvals submitted

---

# PCB terminal block - FFKDSA1/V-2.54-6 - 1789579

## Approvals

### Approval details

CSA		
		B
mm <sup>2</sup> /AWG/kcmil	20	
Nominal current I <sub>N</sub>	6 A	
Nominal voltage U <sub>N</sub>	150 V	

UL Recognized		
		B
mm <sup>2</sup> /AWG/kcmil	26-20	
Nominal current I <sub>N</sub>	6 A	
Nominal voltage U <sub>N</sub>	150 V	

cUL Recognized		
		B
mm <sup>2</sup> /AWG/kcmil	26-20	
Nominal current I <sub>N</sub>	6 A	
Nominal voltage U <sub>N</sub>	150 V	

cULus Recognized		
------------------	--	--