# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



### ZQV 4N/3 SW



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-2083 www.weidmueller.com

Weidmüller offers users of modular terminals of the Z-Series a comprehensive range of accessories that render possible appropriate solutions for all - even non-standard - tasks. The accessories must comply with the same quality standards as the modular terminals themselves.

#### General ordering data

Order No.	<u>1794000000</u>	
Part designation	ZQV 4N/3 SW	
Version	Cross-connector / link for modular terminal, No.	
	of poles: 3	
GTIN (EAN)	4032248233793	
Qty.	60 pc(s).	

## ZQV 4N/3 SW

**Technical data** 



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-2083 www.weidmueller.com

Additional technical data				
Explosion-tested version	No	Installation advice	Direct mounting	
Conductors for clamping	(additional connection)			
Rated current	32 A			
Rating data				
Rated voltage	0 V	Rated current	32 A	
Approvals				
Approvals institutes	GOSTME25			
Classifications				
ETIM 2.0	EC000489	ETIM 3.0	EC000489	
eClass 5.1	27-14-11-40	eClass 6.0	27-14-11-40	