imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




REVISION									
REV.	DESCRIPTION	DATE	APPROVED						
Α	Changed Pin Out (P1)	03-12-07	DP						




FRONT

IEEE 1394 6P/M MOLDING TYPE (TOOLING NO:G102-216)



FRONT

TAPE 100±20 100±20 9



PIN OUT

NOTES:

1. CABLE: UL20276 IEEE1394

[(30AWGx1P+FOIL+SP)x2+24AWGx2C+MYLAR+FOIL+BD]x1 OUTER PVC JACKET: BLACK OD: 5.7 ± 0.2mm PRINTING: "E166307 N AWM 20276 30AWG VW-1 IEEE Std 1394 Compliant"

- 2. CONNECTORS: IEEE 1394 6P MALE TO IEEE 1394 6P MALE
- 3. HOOD: MOLDED TYPE, COLOR: BLACK
- 4. ELECTRICAL TEST:
 - <1>.100% OPEN SHORT & MISS WIRE TEST
 - <2>.INSULATION RESISTANCE: DC400V 10M ohm MIN.
 - <3>.CONDUCTOR RESISTANCE: 3 ohm MAX.
- 5. PACKING: 1PC/POLYBAG

No.	PARTS NAME		SPECIFICATION STANDARD			QTY	REMARKS		
1	6P/M - CONTACT		PHOSPHOR BRONZE / GOLD FLASH			12			
2	6P/M - INSULATOR			PBT/BLACK UL94V-0			2		
3	6P/M - SHELL 1			IRON / NICKEL PLATED			2		
4) 6P/M - SHELL 2			IRON / NICKEL PLATED			2		
5	5) COPPER FOIL			5x10mm			2		
6 6P/M - INNER MOLD				PE NATURAL			2		
7 6P/M - OUTER MOLD)	45P PVC / COLOR: BLACK			2		
8	8 KL02001ABK01A			[(30AWGx1P+FOIL+SP)x2+24AWGx2C+MYLAR +FOIL+BD1x1_COLOR: BLACK			1		
9	MINI 1	ΓIE	PE / BLACK			2			
10	POLYB	AG	PE / 0.08x140x160mm			1			
Dim Tolerance				Qualtek Electronics Corp. WCT DIVISION					
(mm)		(mm)	Part N	^{lumber:} 18					
0-1		0.15	Descr	ription:					
1-6		0.20	IEEE 1394 6P/M - IEEE 6P/M						
6	6-18 0.30						RFV.	٨	
18-50		0.50					REV.	А	
50-120		0.70	Dra	Drawn / Date Checked / Date A		Ар	oproved / Date		
120-250		0.90	B. Grubb		01-25-07	11	JJH / 01-25-07		
250-500		1.20	0	1-25-07	0.2007				