



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Fiber optic contact insert - VC-FSMA-M-2 SET - 1855432

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Quick mounting plug for polymer fiber cable, for the contact carrier module VC-AFOS 2, length: 27 mm, width: 7 mm, 2 pcs. each as set

Product Features

- Clear representation
- For a variety of applications



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	16.5 GRM
Custom tariff number	85367000
Country of origin	Poland

Technical data

Mechanical characteristics

Number of positions	1
Connection profile	F-SMA type 905, IEC 874-2
Fiber type	Polymer fiber
Fiber	Polymer fiber, 980/1000 µm
Insertion/withdrawal cycles	> 100
Tightening torque, min.	0.1 Nm
Tightening torque max.	0.2 Nm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
Degree of protection	IP20

Material data

Housing material	Nickel silver
------------------	---------------

Fiber optic contact insert - VC-FSMA-M-2 SET - 1855432

Technical data

Material data

Contact material	Nickel silver
------------------	---------------

Optical characteristics

Attenuation	< 3 dB
-------------	--------

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209

ETIM

ETIM 2.0	EC000438
ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC000438

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

Approvals

Approvals

Approvals

EAC

Ex Approvals

Fiber optic contact insert - VC-FSMA-M-2 SET - 1855432

Approvals

Approvals submitted

Approval details

EAC

Drawings

