mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HDC housing;bulkhead housing FRONTCOM AR PLUG



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





The FrontCom® Classic inserts and base plates can be freely combined with the corresponding frames.

General ordering data

Order No.	<u>1879230000</u>		
Туре	FRONTCOM AR PLUG		
Version	Frame for holding a Schuko socket		
GTIN (EAN)	4032248474349		
Qty.	1 pc(s).		

HDC housing;bulkhead housing FRONTCOM AR PLUG

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Dimensions and weights			
Length	98 mm	Width	87 mm
Net weight	246 g		
Temperatures			
Operating temperature			
Technical specifications for	D-Sub		
Operating temperature (D-Sub)			
Technical specifications for	RJ45 coupling		
Operating temperature (RJ45 coupling	g)		
Technical specifications for	RJ45 module		
-			
Operating temperature (RJ45 module))		
Technical specifications for	socket		
lleuring been gesteriel (glug er dust)	Stainless steel		16 A
Housing base material (plug socket) Operating temperature (plug socket)	Stainless steel	Nominal current (plug socket)	18 A
Technical data			
Length	98 mm	Operating temperature	
Version	Frame for holding a Schuko socket	Material	Stainless steel
Colour	Black	Storage temperature, max.	80 °C
Storage temperature, min.	-20 °C		80 C
Classifications			
Classifications			
ETINA O O	50000450		50000450
ETIM 2.0	EC000456	ETIM 3.0	EC000456
UNSPSC eClass 6.2	31-16-23-03 27-14-34-02	eClass 5.1 eClass 7.1	27-18-92-17 27-44-05-02
	27-14-34-02		27-44-05-02
Approvals			
Approvals ROHS	Conform		
nuns	Conform		