imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Z-series, Accessories ZQV 6/24 GE



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com



Weidmüller offers users of modular terminals of the Z-Series a comprehensive range of accessories that render possible appropriate solutions for all - even non-standard tasks.

The accessories must comply with the same quality standards as the modular terminals themselves.

General ordering data

Order No.	<u>1908990000</u>	
Туре	ZQV 6/24 GE	
Version	Z-series, Accessories, Cross-connector, For the terminals, No. of poles: 24	
GTIN (EAN)	4032248535309	
Qty.	10 pc(s).	

Z-series, Accessories ZQV 6/24 GE

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Length	192.5 mm	Width	3.1 mm
Height	33.96 mm	Net weight	34.603 g
lemperatures			
Operating temperature		Storage temperature	
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	120 °C
Additional technical data			
Installation advice	Direct mounting	Version	For the terminals
Rated data			
Rated voltage	400 V	Rated current	41 A
Material data			
Material	Wemid	Colour	Yellow
UL 94 flammability rating	V-0		
System specifications			
Product family	Z-series, Accessories		
Classifications			
ETIM 2.0	EC000489	ETIM 3.0	EC000489
UNSPSC	30-21-18-01	eClass 4.1	27-14-11-99
eClass 5.1	27-14-11-40	eClass 6.2	27-14-11-40
eClass 7.1	27-14-11-40		
Approvals			
Approvals			
	MEAF		
	ME25		
ROHS	Conform		

Creation date April 16, 2013 11:01:29 PM CEST