

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









## Accessories - MCC-MT 0,2-0,35 (0,0) BA - 1923717

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Female contact, is inserted into the plug after crimping the conductor, for the module plug housing MCC 1...-STZ-3,81 and MCC 1...-STZF-3,81, for cross sections of 0.2 mm² to 0.34 mm²

Supplied in tape form - please note the drawing.



## Key commercial data

Packing unit	1 pc		
Minimum order quantity	8000 pc		
Weight per Piece (excluding packing)	0.44 GRM		
Custom tariff number	85366990		
Country of origin	Germany		

#### Technical data

#### General

Nominal current	4 A
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Max. conductor cross section, stranded	0.35 mm²

#### Connection data

Core diameter including insulation	1.1 mm 1.3 mm		
Stripping length of individual wires	4 mm		

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701



# Accessories - MCC-MT 0,2-0,35 (0,0) BA - 1923717

## Classifications

### eCl@ss

eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCI@ss 8.0	27440402

### **ETIM**

ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC000438

#### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121410
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

## Approvals

Α	р	p	r	o	٧	а	ls

Approvals

GOST

Ex Approvals

Approvals submitted

Approval details




## Drawings



# Accessories - MCC-MT 0,2-0,35 (0,0) BA - 1923717

#### Dimensioned drawing



Phoenix Contact 2014 © - all rights reserved http://www.phoenixcontact.com