imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



1SV246

PIN Diode Dual series PIN Diode for VHF, UHF and AGC 50V, 50mA, rs=typ 5Ω, MCP



Features

- Series connection of 2 elements in a very small-sized package facilitates high-density mounting and permits 1SV246-applied equipment to be made smaller
- Small interterminal capacitance (C=0.23pF typ)
- Small forward series resistance ($r_s=5\Omega$ typ)

Specifications


Absolute Maximum Ratings at Ta=25°C

| Parameter | Symbol | Conditions | Ratings | Unit |
|-----------------------------|--------|------------|-------------|------|
| Reverse Voltage | VR | | 50 | V |
| Forward Current | IF | | 50 | mA |
| Allowable Power Dissipation | Р | | 100 | mW |
| Junction Temperature | Тј | | 125 | °C |
| Storage Temperature | Tstg | | -55 to +125 | °C |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Package Dimensions

unit : mm (typ) 7023A-007



Product & Package Information


- Package
- JEITA, JEDEC : SC-70, SOT-323

: MCP

• Minimum Packing Quantity : 3,000 pcs./reel


Packing Type: TL

Marking





Electrical Connection




Electrical Characteristics at Ta=25°C


| Parameter | Symbol | Conditions | Ratings | | | Unit |
|---------------------------|--------|-----------------------------|---------|------|-----|------|
| | | | min | typ | max | Unit |
| Reverse Voltage | VR | I _R =10μA | 50 | | | V |
| Reverse Current | IR | V _R =50V | | | 0.1 | μΑ |
| Forward Voltage | VF | IF=50mA | | 0.95 | | V |
| Interterminal Capacitance | С | V _R =50V, f=1MHz | | 0.23 | | pF |
| Series Resistance | rs | IF=10mA, f=100MHz | | 5.0 | | Ω |

Note : The specifications shown above are for each individual diode.

Ordering Information

| Device | Package | Shipping | memo | |
|-------------|---------|----------------|---------|--|
| 1SV246-TL-E | MCP | 3,000pcs./reel | Pb Free | |






Embossed Taping Specification 1SV246-TL-E

1. Packing Format

| Package Name | Carrier Tape | Maximum Number of devices contained (pcs) | | | Packing format |
|---|--------------|--|-----------|-----------|---|
| | Туре | Reel | Inner box | Outer box | Inner BOX (C-1) Outer BOX (A-7) |
| MCP | MCP | 3,000 | 15,000 | 90,000 | 5 reels contained 6 inner boxes contained |
| | | | | | Dimensions:mm (external) Dimensions:mm (external) |
| | | | | | 183×72×185 440×195×210 |
| Packing method 183×72×185 440×195×21 Packing method (unit:mm) Outer box label (unit:mm) It is a label at the time of factory sh The form of a label may change in physi distribution process. Type No. LOT No. Quantity 69 108 Origin Immunitered in the time of factory sh Type No. LOT No. Quantity Immunitered in the time of factory sh Type No. LOT No. Quantity Immunitered in the time of factory sh type No. LOT No. Quantity Origin Immunitered in the time of factory sh type No. LOT No. Quantity Immunitered in the time of factory sh type No. LOT No. Quantity Immunitered in the time of the terminal is lead free. Immunitered in the time of factory sh type No. LOT No. Quantity Immunitered in the terminal is lead free. Immunitered in the terminal is lead free. NOTE (I) The LEAD FREE % description shows that the surface treatment of the terminal is lead free. LEAD FREE 4 JEITA Phase 3 LEAD FREE 4 | | | | | |

2. Taping configuration

2-1. Carrier tape size (unit:mm)




Those with oen electrode terminal on the feed hole side $\cdots TL$


ΤL

Carrier tape

Outline Drawing 1SV246-TL-E



Land Pattern Example



ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typical" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemity and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal