

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



### Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







# Model 1Z0280-3



## **Hybrid Couplers**

High Power 3 dB, 90°

#### **Applications**

- Microstrip Circuits
- Power Amps
- Divider/Combiners
- Switch Networks
- **Balanced Detectors**
- Antenna Feeds




#### **Features**

- Welded Tab Mount
- 2-Way Power Split
- Reliable Performance
- Handles 700 Watts

Electrical Specifications			
Frequency MHz	Isolation dB Min/Typ	Insert. Loss dB Max	VSWR Max : 1
100 - 160	23	0.25	1.15
Amp. Bal. dB Max	Phase Bal.  Degrees Max	Power Ave. CW Watts	
±0.40	±2.0	700	

Notes: Impedance: 50 ohms nominal. Meets MIL-E-5400 Class 3 requirements. Additional screening available for military and space applications. Electrical specifications apply only properly designed test fixtures. Testing is done at ambient temperature only. Sample testing is performed to MIL-Std-105, Level 2, AQL 1.0. Test includes coupling, amplitude balance, insertion loss and isolation. If your application requires additional testing, consult Anaren Power rating applies when solder tab/coupler interface has been conformally coated.

Electrical and Mechanical Specifications subject to change without notice.



Sales Desk USA: Voice: (800) 544-2414 Fax: (315) 432-9121 Sales Desk Europe: Voice: (+44) 23 92 232392 Fax: (+44) 23 92 251369