



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





tightening torque/thread 1.0 Nm/M 3 Inspection Test Pattern Size A 4

Type	Cat.-No.		Qty.p.pck.
<b>SR 4 DRL</b>	41211.2	beige	100
<b>SR 4 DRL</b>	41211.5	blue	100


### Ratings:

	UL	CSA	DIN-VDE	IEC
Rated Voltage	600 V	600 V	500 V	500 V
Rated Current	20 A AWG 12	26 A	26 A	24 A

### Max Rated Cross Section

Single Wire (solid)	0.2-4 mm <sup>2</sup>
Stranded Wire (flexible)	0.2-2.4 mm <sup>2</sup>
Wire Size	AWG 22-12

Dimensions	TS 32	TS 35
LxBxH (mm)	67x6x52	67x6x47
Stripped Length	9 mm	



tightening torque/thread 2.0 Nm/M 4 Inspection Test Pattern Size A 5

Type	Cat.-No.		Qty.p.pck.
<b>SR 10</b>	41005.2	beige	100
<b>SR 10</b>	41005.5	blue	100

Additional colors available. See page 114.

### Ratings:

	UL	CSA	DIN-VDE	IEC
Rated Voltage	600 V	600 V	750 V	800 V
Rated Current	65 A AWG 8	55 A	61 A	57 A

### Max Rated Cross Section

Single Wire (solid)	0.2-10 mm <sup>2</sup>
Stranded Wire (flexible)	0.2-10 mm <sup>2</sup>
Wire Size	AWG 22-8

Dimensions	TS 32	TS 35
LxBxH (mm)	48x8x52	48x8x47
Stripped Length	12 mm	

Type:	Cat.-No.	Qty.p.pck.	Terminal accessories	Type:	Cat.-No.	Qty.p.pck.
AP 2.5 RL	2575.2 beige 2575.5 blue	50	End plate	AP 2.5-10	2001.2 beige 2001.5 blue	50
			Isolation partition	TW 2.5-10	2002.2 beige 2002.5 blue	50
TRS 1	2003.2 beige	100	Separator	TRS 1	2003.2 beige	100
ES 32/35 Combi	1424.2 beige		End bracket	ES 32/35 Combi	1424.2 beige	
ES 32/K/ST	2827.0	50		ES 32/K/ST	2827.0	50
ES 35/2/K	2826.2 beige		End bracket	ES 35/2/K	2826.2 beige	
ES 35/K/ST	2828.0	50		ES 35/K/ST	2828.0	50
STB 14/2.3	2006.0	50	Test socket	STB 14/4	2050.0	50
PS 2.3	2007.0	20	Test plug	PS 4	2051.0	20
QL 2	2008.0	50	Switchable link	QL 2	2053.0	50
VH 19	2009.0	100	Connection sleeve	VH 19	2009.0	100
BS M 3x25	2010.0	100	Screw	BS M 3x25	2010.0	100
AD 4	2011.0	50	Warning tag (German)	AD 4	2054.0	50
AD 4 E	2494.0	50	Warning tag (English)	AD 4 E	2495.0	50
BSK M 3x22	2012.0	100	Plastic screw for warning tag	BSK M 3x22	2012.0	100
Q2/Q1 2	2019.0/2740.2	50	Cross-connection/Insulated cross-connection	Q2/Q1 2	2060.0/2750.2	50
Q3/Q1 3	2020.0/2741.2	50	Cross-connection/Insulated cross-connection	Q3/Q1 3	2061.0/2751.2	50
Q4/Q1 4	2021.0/2742.2	20	Cross-connection/Insulated cross-connection	Q4/Q1 4	2062.0/2752.2	20
Q10/Q1 10	2022.0/2743.2	10	Cross-connection/Insulated cross-connection	Q10/Q1 10	2063.0/2753.2	10