



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## Accessories

### Ha-VIS SFP modules 1000 Mbit/s

#### SFP:

| Type                  | SFP Gigabit Ethernet Transceiver 1.25 Gbit/s MM | SFP Gigabit Ethernet Transceiver 1.25 Gbit/s SM | SFP Gigabit Ethernet Transceiver 1.25 Gbit/s SM | SFP Gigabit Ethernet Transceiver 1.25 Gbit/s SM |
|-----------------------|---|---|---|---|
| Wave length           | 850 nm  | 1310 nm   | 1310 nm   | 1310 nm   |
| Mode                  | Multimode                                       | Singlemode                                      | Singlemode                                      | Singlemode                                      |
| Fiber                 | 50 / 125 µm or 62.5 / 125 µm                    | 9 / 125 µm                                      | 9 / 125 µm                                      | 9 / 125 µm                                      |
| Max. cable length*    | 550 m (50 / 125)<br>275 m (62.5 / 125)          | 10 km   | 40 km   | 80 km   |
| Connector             | LC connector duplex                             | LC connector duplex                             | LC connector duplex                             | LC connector duplex                             |
| Optical budget        | min. 9 dB                                       | min. 9 dB                                       | min. 9 dB                                       | min. 9 dB                                       |
| Data rate             | 1250 Mbit/s                                     | 1250 Mbit/s                                     | 1250 Mbit/s                                     | 1250 Mbit/s                                     |
| Operating temperature | -40 °C ... +70 °C                               | -40 °C ... +70 °C                               | -40 °C ... +70 °C                               | -40 °C ... +70 °C                               |

\* Typical cable length depending on attenuation of each specific application.

| Identification | Part number | Drawing | Dimensions in mm |
|----------------|-------------|---------|------------------|
|----------------|-------------|---------|------------------|

#### SFP modules

|   |                |  |
|---|----------------|--|
| SFP Gigabit Ethernet Transceiver 1,25 Gbit/s MM     | 20 76 010 0300 |  |
| SFP Gigabit Ethernet Transceiver 1,25 Gbit/s SM     | 20 76 030 0300 |  |
| SFP Gigabit Ethernet Transceiver L40 1,25 Gbit/s SM | 20 76 034 0300 |  |
| SFP Gigabit Ethernet Transceiver L80 1,25 Gbit/s SM | 20 76 038 0300 |  |
| other types on request                              |                |  |