imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Cylindrical House Service Cut-Out Fuse Links and Modular Fuse Holder KR85 Fuse Link



Catalogue Symbol: (Amp rating)KR85

gG


Class of Operation:

See page 7 and 8 for details

ø22 2

Dimensions - mm:

Fuse Holders:



Amp Rating/ Catalogue Number		Nom. Watts		
	Pre-Arcing	Total at 240V	Total at 415V	Loss
5KR85	8.4	15	23.5	2.5
10KR85	84	150	235	3.3
15KR85	53	90	130	2.9
20KR85	215	360	510	2.6
25KR85	480	815	1150	2.8
30KR85	1000	2700	5700	3.0
40KR85	2500	6800	14000	3.8
45KR85	3600	9880	20500	3.8
50KR85	4720	13000	27000	4.2
60KR85	9100	25000	52000	4.3
70KR85	17000	29000	40500	4.8
80KR85	24500	41500	58500	5.4
90KR85*	33000	56500	79500	5.7
100KR85*	43500	73500	105000	6.1

* Not recommended for use in the UK. If 90A or 100A fuse links are required in the UK please use Cooper Bussmann 100LR85 and Cooper Bussmann 100SP fuse holder instead.

Standards/Approvals:	 ASTA Certified BS1361: 1971 including amendments 1, 2 and 3
Description:	Designed for use in conventional house service cut-outs (Cooper Bussmann part number 6080SP)
Packaging:	Pack quantity: 20 MOQ: 20
Technical Data: Rated voltage: Amps:	415Vac 5 to 100A


Rated breaking capacity: 33kA

06-09 BU-SB09485


Page 1 of 8

Data Sheet 720114 COOPER Bussmann

Cylindrical House Service Cut-Out Fuse Links and Modular Fuse Holder KR85 Fuse Link



Time-Current Curve Characteristics




COOPER

Bussmann


Data Sheet 720114 **COOPER Bussmann**


Cylindrical House Service Cut-Out Fuse Links and Modular Fuse Holder KR85 Fuse Link



Cut-Off Current Curves

Cylindrical House Service Cut-Out Fuse Links and Modular Fuse Holder LR85 Fuse Link





COOPER


Bussmann

Amp Rating/ Catalogue Number	I²t (Amp² Seconds)			Nom. Watts
	Pre-Arcing	Total at 240V	Total at 415V	Loss
30LR85	1200	2300	3600	3.4
40LR85	3680	6900	11000	3.5
50LR85	6360	12000	19100	4.1
60LR85	12700	24000	38100	4.5
80LR85	13200	38100	82500	4.9
100LR85	26900	57300	99500	5.0



BUSSMann

Cylindrical House Service Cut-Out Fuse Links and Modular Fuse Holder LR85 Fuse Link



Time-Current Curves Characteristics




06-09 BU-SB09485

Page 5 of 8



Cylindrical House Service Cut-Out Fuse Links and Modular Fuse Holder LR85 Fuse Link



Cut-Off Current Curves



06-09 BU-SB09485



Cylindrical House Service Cut-Out Fuse Links and Modular Fuse Holder Fuse Holder



Part Numbers:

100SP:	Single-pole unit 60/80A Single-pole unit 100A
6080SP:	Single pole unit 60/800

CNE-HS:Single-pole combined neutral and earth moduleSNE-HS:Single-pole separate neutral and earth module

Standards/Approvals:	BS 7657Third party verified
Description:	House service cut-out for use with house service fuse links, Cooper Bussmann part numbers KR85 / LR85 or equivalent.
Packaging:	Pack quantity: 10 MOQ: 10
Technical Data: Rated voltage: Amps:	415Vac 60/80A and 100A

Accessory Catalogue Numbers

Rated breaking capacity: as per BS 1361, 33kA

SP-HS-COVER: Single-pole and neutral crutch cover TP-HS-COVER: Three-pole and neutral crutch cover SPARES-KITS-HS: 2 grommets, 2 "H' mouldings, 1 adaptor, 1 screw TOOL-HS: Cable entry plug removal tool

Features:

- Modularity
- Thermally efficient
- Ease of installation
- Reverse polarity
- Third party approved

6080SP/100SP



SNE-HS/CNE-HS






SP-HS-COVER

TP-HS-COVER






Page 7 of 8




Cylindrical House Service Cut-Out Fuse Links and Modular Fuse Holder Modular Fuse Holder

Modular Fuse Holder Dimensions - mm






Single-Pole and CNE or SNE Configuration



Three-pole and CNE or SNE configuration



 \geq

267

Modular Fuse Holder Recommended Torque Values

661

