



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



211-60120

Article Number: 211-60120

P Clamp, .39" Width, .75" Max Bundle Dia, .17" Mounting Hole Dia, PA66HS, Black, 1000/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 211-60120

Type H11P

Color Black (BK)

Features and Benefits

- P-Clamps easily guide and locate wire and cables up to 1" in diameter.
- Designed with a radiused edge to prevent chaffing and cutting into insulation.

Product Description HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1" bundle diameters.

Fixation Method (FF) screw-hole

Variant Closed

Short Description P Clamp, .39" Width, .75" Max Bundle Dia, .17" Mounting Hole Dia, PA66HS, Black, 1000/pkg

Product Dimensions

Width W (Imperial) 0.39 "

Width W (Metric) 10.0 mm

Bundle Diameter Max. (Imperial) 0.75 "

Bundle Diameter Max. (Metric) 19.0 mm

Mounting Hole Diameter D (Imperial) 0.17 "

Mounting Hole Diameter D (Metric) 4.2 mm

Nominal Diameter (Imperial) 3/4 "

Nominal Diameter (Metric) 19 mm

Wall Thickness WT (Imperial) .05906 "

Wall Thickness WT (Metric) 1.5 mm

Mounting Hole Centers (Imperial) 0.71 "

Mounting Hole Centers (Metric) 18.0 mm

Radius R (imperial) 0.08 "

Radius R (metric) 2.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000 Pieces

Carton Quantity 4000 Pieces

Weight (Metric) 1.3 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS compliant (Article 4 - 1) Yes