



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# High-Temperature Masking Tape

## 214

**Technical Data**

**February 2016**

### Product Description

Scotch® High-temperature Masking Tape 214 is good for 30 minutes at 350°F (177°C) on most surfaces. The adhesive is sulfur-free which makes it one of the few tapes that can be used on copper, silver and other precious metals.

### Product Construction

Backing	Adhesive	Standard Roll Length
Smooth crepe paper treated with a high heat and stain resistant saturant	Firm rubber adhesive designed to give outstanding holding power for a high heat resistant tape	60 yds. (54.8 m)

### Typical Physical Properties

**Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	29 oz./in. width (32 N/100 mm)	D-3330
Tensile Strength:	27 lbs./in. width (480 N/100 mm)	D-3759
Elongation at Break:	10%	D-3759
Tape Thickness:	5.5 mils (.140 mm)	D-3652
Temperature Use Range:	Up to 350°F (177°C)	

### Features

- Has excellent stain resistance.
- Adhesive is very firm and allows it to be used on most treated metals.
- Scotch® Tape 214 complements Scotch® Tape 213 in high temperature masking tape usage and should be evaluated at the same time.
- Will generally withstand bake cycles up to 350°F (177°C) for 30 minutes – even on treated metals. Performance is governed by total time, temperature, surface tape is applied to, and any other coatings and conditions.
- Should not be subjected to outdoor exposure or prolonged periods of sunlight exposure as tape may become very difficult to remove.

### Application Ideas

- Can be used in a wide variety of high heat, treated metal, and stain resistant applications. It is generally considered only when one of these factors is a problem.

# Scotch® High-temperature Masking Tape

214

---

**Storage** Store under normal conditions of 60° to 80°F (16° to 27°C) and 40-60% R.H. in the original carton.

---

**Shelf Life** To obtain best performance, use this product within 12 months from date of shipment.

---

**Technical Information** The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

---

**Product Use** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

---

**Warranty, Limited Remedy, and Disclaimer** Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

---

**Limitation of Liability** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

---

**ISO 9001**

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.



## Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
800-362-3550 • 877-369-2923 (Fax)  
www.3M.com/industrial



Recycled Paper  
40% pre-consumer  
10% post-consumer

Scotch is a registered trademark of 3M. Printed in U.S.A.  
©3M 2016 (E) 70070945558 (2/16)