



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## #2200 Irradiated PVC Hook-Up Wire

UL Style 1429 · VW-1 · CSA AWM ·  
XLPVC MIL-W-16878 · TYPE B · 600V

**Description:** One conductor, tinned copper with .010" irradiated PVC insulation (XLPVC). Daburn's irradiated PVC Hook-up wire is made from extruded polyvinyl chloride insulation which has been exposed to controlled radiation. This exposure causes the insulation to become far superior to ordinary PVC in temperature, abrasion and cut-through resistance. It can withstand direct contact with a soldering iron and it will not shrink back, melt or deform. Ideal for hi-density wiring.

**Temperature Rating:** -55°C to +105°C (UL 1429: 80°C.)

**Voltage Rating:** Type B, 600V, (UL 1429: 150V).

This series is RoHS compliant.

| DABURN<br>Cat. No. | Size<br>AWG | Strand | Nom. O.D. |      | Standard<br>Packaging |
|--------------------|-------------|--------|-----------|------|-----------------------|
|                    |             |        | IN.       | MM.  |                       |
| 2200/28            | 28          | 7/36   | 0.035     | 0.89 | 100', 1000'           |
| 2200/26            | 26          | 7/34   | 0.040     | 1.02 | 100', 1000'           |
| 2200/24            | 24          | 7/32   | 0.045     | 1.14 | 100', 1000'           |
| 2201/24            | 24          | 19/36  | 0.046     | 1.17 | 100', 1000'           |
| 2200/24S*          | 24          | SOLID  | 0.041     | 1.04 | 100', 1000'           |
| 2201/22            | 22          | 19/34  | 0.052     | 1.32 | 100', 1000'           |
| 2200/22            | 22          | 7/30   | 0.051     | 1.30 | 100', 1000'           |
| 2200/22S*          | 22          | SOLID  | 0.046     | 1.17 | 100', 1000'           |
| 2201/20            | 20          | 19/32  | 0.059     | 1.50 | 100', 1000'           |
| 2200/20            | 20          | 7/28   | 0.060     | 1.52 | 100', 1000'           |
| 2200/20S*          | 20          | SOLID  | 0.054     | 1.37 | 100', 1000'           |
| 2201/18            | 18          | 19/30  | 0.070     | 1.78 | 100', 1000'           |
| 2200/18            | 18          | 7/26   | 0.070     | 1.78 | 100', 1000'           |
| 2200/16            | 16          | 19/29  | 0.078     | 1.98 | 100', 1000'           |

**Standard Colors:** White, Black, Red, Green, Yellow, Blue, Brown, Orange, Gray, Violet. Additional colors, sizes and constructions to order. Additional mil spec constructions are available to MIL-W-16878/14, MIL-W-16878/15 and MIL-W-16878/16.

\* Not Mil Spec Approved.