imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Electronic housing - ME MAX 67,5 U-U1 KMGY - 2200547

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Product Features

- Plug-in connection with screw, spring-cage or fast connection technology
- ☑ Labels for additional labeling as an option
- DIN rail bus connector as an option
- ☑ Large front surface for high-pos. plugs or operating and setting elements
- ☑ Large PCB surface despite compact housing dimensions
- ☑ Easy module replacement without interrupting the contact chain
- ☑ The fitted cover is easy to adapt and print
- Functional earth ground contact as an option
- G Fixed or plug-in connection technology can be combined on up to three connection levels, with different pitches
- ☑ Transparent front cover can be swiveled

Key commercial data

Packing unit	11
Minimum order quantity	10 1
Weight per Piece (excluding packing)	200.0 GRM
Custom tariff number	85472000
Country of origin	Germany

Technical data

General

Housing type	Complete housing
Housing material	Polyamide
Color	light gray

Ambient conditions

Ambient temperature (operation) -40 °C 105 °C

Dimensions



Electronic housing - ME MAX 67,5 U-U1 KMGY - 2200547

Technical data

Dimensions

Length	99 mm
Constructional height	114.5 mm
Width	67.5 mm

Technical data

Inflammability class according to UL 94	V0
Power dissipation at 20°C in the horizontal mounting position	9.1 W 17.5 W
Number of positions	12

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702

ETIM

ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com