

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









# Electronic housing - ME-IO 18,8 C 2U 7035 - 2201799

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Component housing, length: 21.8 mm, Cover, color: light gray, width: 18.9 mm, height: 12.2 mm

### Why buy this product

- ▼ Tool-free mounting
- ✓ Available in overall widths from 18.8 mm
- ☑ Inflammability class V0 according to UL 94
- Front push-in connection technology
- Can be mounted on the DIN rail
- Optional with bus connector for DIN rail mounting



# **Key Commercial Data**

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	4 046356 911603
GTIN	4046356911603

### Technical data

#### General

Housing type	Component housing
Housing material	Polyamide
Color (RAL)	light gray

### Ambient conditions

Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)
---------------------------------	--

#### **Dimensions**

Length	21.8 mm
Constructional height	12.2 mm



# Electronic housing - ME-IO 18,8 C 2U 7035 - 2201799


# Technical data

## Dimensions

Width	18.9 mm	
Technical data		
Number of positions	5	
Standards and Regulations		
Flammability rating according to UL 94	V0	
Environmental Product Compliance		
China RoHS	Environmentally friendly use period: unlimited = EFUP-e	


# **Drawings**

#### Dimensional drawing



### Dimensional drawing

No hazardous substances above threshold values



# Approvals

# Approvals

Approvals

UL Recognized / EAC

Ex Approvals

### Approval details

UL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 240868

EAC **EAC** B.01742



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

08/18/2018 Page 3 / 3