

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









FlashtecTM NVRAM Drive Family NV1616 and NV1604 Flashtec PCIe NVRAM Drives

The Microsemi Flashtec™ NVRAM Drive family provides a PCI Express NVRAM solution based on the most advanced NVMe controller on the market. This family provides a new level of performance to the memory/storage hierarchy, ushering storage system OEMs, cloud applications, and service providers to the era of storage-class memory.

Establishes New Storage Tier with Superior Performance

- Non-volatile DRAM-like performance, NAND persistence
- Over 10 million IOPS (direct memory mode, available for NV1616 only)
- Sub-microsecond latency

Ease-of-Use for Faster Time to Market

- Industry-standard interfaces
- Application-friendly for ease of integration
- Zero maintenance green backup
- "Enterprise Class" for mission-critical data center
- Uncompromising quality and reliability
- Unlimited endurance NVRAM
- Small form factor for high-density rack solutions

Cloud-Scale Performance and Availability

While SSD solutions continue to replace traditional HDDs in the performance tier of the storage hierarchy, there remains a significant performance gap between the memory tiers and the storage tiers in terms of latency, endurance, and high availability. As application demands continue to increase at an ever growing pace to keep up with the growth rate of cloud services, relying on volatile memory to achieve desired performance leaves applications vulnerable to data loss in the event of a system failure.

There is a need for a new tier of memory that provides mission-critical applications with the necessary safety net for their data while keeping pace with the application requirements for performance without compromising data protection, reliability, and availability.

Flashtec NVRAM Drive products serve exactly that need, and with >10M IOPS and up to 16 GB of memory per card, the product family can address the needs of the most demanding applications.

Lower Total Cost of Ownership (TCO)

Power failure protection is built into Flashtec NVRAM Drive products. A flash-based backup unit protects DRAM content in the event of a power failure. This backup unit eliminates the Uninterruptible Power Supply (UPS) or Backup Battery Unit (BBU), frees up rack space, and reduces support and maintenance costs without compromising critical system data across power failures.



Highlights

- Unlimited endurance: unlike SSDs, DRAM has practically unlimited endurance, and with up to 16 GB of non-volatile DRAM memory, NVRAM drives can fit very demanding workloads as well
- High-performance I/O: 1 million IOPS in NVMe block mode (512 B); over 10 million IOPS in direct memory mode
- Power failure protection: flash-based backup unit protects DRAM content in the event of a power failure
- Higher availability: a fast backup and recovery cycle ensures that mission-critical applications will have a shorter recovery time across power failure events
- Lower TCO: eliminating the Uninterruptible Power Supply (UPS) or Backup Battery Unit (BBU) frees up rack space and reduces support and maintenance costs without compromising critical system data across power failures

Applications

- Write cache for low-latency response time
- 64-bit addressable persistent metadata memory region
- Persistent shared memory for scale-out clustered systems
- High-performance journaling or write ahead logging
- · Persistent cache for fast cache rebuild
- Performance tier de-staging to sequentialaccess capacity tier

Included

- NVRAM card
- SCM-F100/F35 module and cable




FlashtecTM NVRAM Drive Family NV1616 and NV1604 Flashtec PCIe NVRAM Drives

Features

Host interface x8 lane PCI express 3.0 Form factor Low profile MD2 PCIe add-in card Access modes Block mode and direct memory mode Memory capacity 4/16 GB configurations Backup store Flash module Data retention offline 3 months Backup power supply Tethered super capacitor mode Restore time <15 sec Backup time <20 sec Backup cycles Up to 3000 Monitoring and alerts Yes Hardware Support Driver support industry Supported NVMe drivers Application support NV-lib for application integration Data Protection and Security Authentication Operating temperature 0 °C to 50 °C at 200 LFM Power consumption <20 W typical; 5 W idle Reliability Maintenance No maintenance required Operational lifetime 5 years Compliance and Certification NVMe.org NVMe 1.0 compatible PCIe SIG Certified				
PCI express Form factor Low profile MD2 PCIe add-in card Access modes Block mode and direct memory mode Memory capacity 4/16 GB configurations Backup store Flash module Data retention offline Backup power supply Tethered super capacitor mode Restore time Sackup time Sackup time Sackup cycles Backup cycles Backup oycles Up to 3000 Monitoring and alerts Hardware Support Driver support industry Application support NV-lib for application integration Data Protection and Security Authentication Mechanical and Environmental Form factor Operating temperature Operating temperature Operational lifetime Syears Compliance and Certification NVMe.org NVMe 1.0 compatible	General Features			
Form factor Access modes Block mode and direct memory mode Memory capacity 4/16 GB configurations Backup store Flash module Data retention offline Backup power supply Tethered super capacitor mode Restore time Capacity Access modes Backup power supply Tethered super capacitor mode Restore time Capacity Capacity Restore time Capacitor mode Capac	Host interface	x8 lane		
Access modes Memory capacity A/16 GB configurations Backup store Data retention offline Backup power supply Tethered super capacitor mode Restore time Backup time Capacity Authentication Mechanical and Environmental Form factor Operating temperature Operational lifetime Slock mode and direct memory mode 4/16 GB configurations Flash module 3 months Tethered super capacitor mode Authered super capacitor mode Aut	PCI express	3.0		
Memory capacity Backup store Flash module Data retention offline Backup power supply Tethered super capacitor mode Restore time Sackup time Restore time Sackup time Sackup cycles Backup cycles Backup cycles Up to 3000 Monitoring and alerts Hardware Support Driver support industry Supported NVMe drivers Application support NV-lib for application integration Data Protection and Security Authentication Sequence Mechanical and Environmental Form factor MD2 low profile PCle card Operating temperature Operating temperature Operating temperature No maintenance required Operational lifetime Syears Compliance and Certification NVMe.org NVMe 1.0 compatible	Form factor	Low profile MD2 PCIe add-in card		
Backup store	Access modes	Block mode and direct memory mode		
Data retention offline Backup power supply Restore time R	Memory capacity	4/16 GB configurations		
Backup power supply Restore time Restore tim	Backup store	Flash module		
Restore time Backup time Restore time Backup cycles Backup cycles Up to 3000 Monitoring and alerts Hardware Support Driver support industry Application support Data Protection and Security Authentication Authentication Mechanical and Environmental Form factor Operating temperature Power consumption Reliability Maintenance Operational lifetime Some Analysis and Environmental Form factor Operational Reliability Maintenance No maintenance required Operational lifetime Some Analysis and Source Ves No maintenance required Operational lifetime Some Analysis and Source Ves No maintenance required Operational lifetime No maintenance required No maintenance required No maintenance required No maintenance required Operational lifetime No maintenance required Operational lifetime No maintenance required	Data retention offline	3 months		
Backup time <20 sec Backup cycles Up to 3000 Monitoring and alerts Yes Hardware Support Driver support industry Supported NVMe drivers Application support NV-lib for application integration Data Protection and Security Authentication Optional host authentication sequence Mechanical and Environmental Form factor MD2 low profile PCle card Operating temperature 0 °C to 50 °C at 200 LFM Power consumption <20 W typical; 5 W idle Reliability Maintenance No maintenance required Operational lifetime 5 years Compliance and Certification NVMe.org NVMe 1.0 compatible	Backup power supply	Tethered super capacitor mode		
Backup cycles Monitoring and alerts Hardware Support Driver support industry Application support Data Protection and Security Authentication Mechanical and Environmental Form factor Operating temperature Power consumption Reliability Maintenance Operational lifetime Optional host authentication sequence MD2 low profile PCle card O°C to 50 °C at 200 LFM < 20 W typical ; 5 W idle Reliability Maintenance Operational lifetime 5 years Compliance and Certification NVMe.org NVMe 1.0 compatible	Restore time	Restore time <15 sec		
Monitoring and alerts Hardware Support Driver support industry Application support Data Protection and Security Authentication Mechanical and Environmental Form factor Operating temperature Power consumption Reliability Maintenance Operational lifetime Operational lifetime Supported NVMe drivers NV-lib for application integration Optional host authentication sequence MD2 low profile PCle card O °C to 50 °C at 200 LFM <a href<="" td=""><td>Backup time</td><td><20 sec</td>	Backup time	<20 sec		
Hardware Support Driver support industry Application support Data Protection and Security Authentication Mechanical and Environmental Form factor Operating temperature Power consumption Reliability Maintenance Operational lifetime Operational lifetime Supported NVMe drivers NV-lib for application integration Optional host authentication sequence MD2 low profile PCle card O °C to 50 °C at 200 LFM <20 W typical; 5 W idle Reliability No maintenance required Operational lifetime 5 years Compliance and Certification NVMe.org NVMe 1.0 compatible	Backup cycles	Up to 3000		
Driver support industry Application support NV-lib for application integration Data Protection and Security Authentication Mechanical and Environmental Form factor Operating temperature Power consumption Reliability Maintenance Operational lifetime Operational lifetime Supported NVMe drivers NV-lib for application integration Optional host authentication sequence MD2 low profile PCle card O°C to 50°C at 200 LFM <20 W typical; 5 W idle Reliability No maintenance required Operational lifetime S years Compliance and Certification NVMe.org NVMe 1.0 compatible	Monitoring and alerts	Yes		
Application support Data Protection and Security Authentication Optional host authentication sequence Mechanical and Environmental Form factor Operating temperature Power consumption Reliability Maintenance Operational lifetime Operational lifetime Syears Compliance and Certification NVMe.org NV-lib for application integration NVJ-lib for application integration	Hardware Support			
Data Protection and Security Authentication Optional host authentication sequence Mechanical and Environmental Form factor Operating temperature O°C to 50 °C at 200 LFM Power consumption Reliability Maintenance Operational lifetime Syears Compliance and Certification NVMe.org No maintenance NVMe 1.0 compatible	Driver support industry	Supported NVMe drivers		
Authentication Optional host authentication sequence Mechanical and Environmental Form factor Operating temperature O °C to 50 °C at 200 LFM Power consumption Reliability Maintenance Operational lifetime S years Compliance and Certification NVMe.org No maintenance NVMe 1.0 compatible	Application support	NV-lib for application integration		
Mechanical and Environmental Form factor MD2 low profile PCle card Operating temperature 0 °C to 50 °C at 200 LFM Power consumption <20 W typical; 5 W idle Reliability Maintenance No maintenance required Operational lifetime 5 years Compliance and Certification NVMe.org NVMe 1.0 compatible	Data Protection and Security			
Form factor MD2 low profile PCle card Operating temperature 0 °C to 50 °C at 200 LFM Power consumption <20 W typical; 5 W idle Reliability Maintenance No maintenance required Operational lifetime 5 years Compliance and Certification NVMe.org NVMe 1.0 compatible	Authentication	·		
Operating temperature O °C to 50 °C at 200 LFM Power consumption Reliability Maintenance Operational lifetime S years Compliance and Certification NVMe.org NVMe 1.0 compatible	Mechanical and Environmental			
Power consumption <20 W typical; 5 W idle Reliability Maintenance No maintenance required Operational lifetime 5 years Compliance and Certification NVMe.org NVMe 1.0 compatible	Form factor	MD2 low profile PCIe card		
Reliability Maintenance No maintenance required Operational lifetime 5 years Compliance and Certification NVMe.org NVMe 1.0 compatible	Operating temperature	0 °C to 50 °C at 200 LFM		
Maintenance No maintenance required Operational lifetime 5 years Compliance and Certification NVMe.org NVMe 1.0 compatible	Power consumption	<20 W typical; 5 W idle		
Operational lifetime 5 years Compliance and Certification NVMe.org NVMe 1.0 compatible	Reliability			
Compliance and Certification NVMe.org NVMe 1.0 compatible	Maintenance	No maintenance required		
NVMe.org NVMe 1.0 compatible	Operational lifetime	5 years		
	Compliance and Certification			
PCIe SIG Certified	NVMe.org	NVMe 1.0 compatible		
	PCIe SIG	PCIe SIG Certified		


Further resources and information can be found at: http://www.microsemi.com/products/storage/storage

Block Mode Access



Configuration & Management

Direct Memory Access



Ordering Information

Model	Description	Part Number
NV1616	16 GB NVRAM PCle drive and SCM-F100	2284700-R
NV1604	4 GB NVRAM PCIe drive and SCM-F35	2285400-R



Microsemi Corporate Headquarters

One Enterprise, Aliso Viejo, CA 92656 USA Within the USA: +1 (800) 713-4113 Outside the USA: +1 (949) 380-6100 Fax: +1 (949) 215-4996 Email: sales.support@microsemi.com www.microsemi.com

©2018 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners. Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California and has approximately 4,800 employees globally. Learn more at www.microsemi.com.

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine subability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.