



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Interface module - FLKM 16/ZFKDS - 2302900

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Standard 1:1 FLK module, with spring-cage connection and flat-ribbon cable connector, no. of positions 16

The illustration shows a 40-position version



Key commercial data

Packing unit	1 PCE
GTIN	 4 017918 941420
Custom tariff number	85369010
Country of origin	GERMANY

Technical data

Dimensions

Width	45 mm
Height	77 mm
Depth	51 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Nominal voltage U_N	< 50 V AC
	60 V DC
Max. current carrying capacity per branch	1 A
Number of positions	16
Mounting position	Any

Interface module - FLKM 16/ZFKDS - 2302900

Technical data

General

Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103

Connection data for connection 1

Connection name	PCB connection
Connection method	Spring-cage connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

Connection data for connection 2

Connection name	Flat-ribbon cable connection
Number of connections	1
Connection method	IDC/FLK pin strip (2.54 mm)
Number of positions	16

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27242608
eCl@ss 7.0	27141152
eCl@ss 8.0	27141152

ETIM

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC002780

UNSPSC

UNSPSC 6.01	30211824
-------------	----------

Interface module - FLKM 16/ZFKDS - 2302900

Classifications

UNSPSC

UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

Accessories

Accessories

Cable/conductor

Cable - FLK 16/EZ-DR/ 50/KONFEK - 2299291



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 0.5 m

Cable - FLK 16/EZ-DR/ 100/KONFEK - 2299301



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 1 m

Cable - FLK 16/EZ-DR/ 150/KONFEK - 2299314



Round cable set, with two 16-pos. socket strips, (1:1 connection), cable length: 1.5 m

Cable - FLK 16/EZ-DR/ 200/KONFEK - 2299327



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 2 m

Interface module - FLKM 16/ZFKDS - 2302900

Accessories

Cable - FLK 16/EZ-DR/ 300/KONFEK - 2299330



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 3 m

Cable - FLK 16/EZ-DR/ 400/KONFEK - 2299343



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 4 m

Cable - FLK 16/EZ-DR/ 800/KONFEK - 2299369



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 8 m

Cable - FLK 16/EZ-DR/1000/KONFEK - 2299372



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 10 m

Cable - FLK EZ-DR.../.../... - 2295059



Round cable, with preassembly, not shielded, variable cable length

Drawings

Interface module - FLKM 16/ZFKDS - 2302900

Circuit diagram

