



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Control cabinet - FB-15-SS - 2316190

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Stainless steel field junction box with 15 ports for use in hazardous locations. Includes FB-ET trunk module, Plugrab base with option for surge protection plug, and DIN rail space for up to 12 device couplers.

### Product Features

- ✓ Cable glands, plugs, and breather must be ordered separately
- ✓ Developed specifically for field device coupler systems
- ✓ Each housing has M20 ports and can be configured as desired
- ✓ Busbar and shield clamps
- ✓ Includes an FB-ET trunk line module and enables the installation of additional couplers and PT plugs
- ✓ Entries for the trunk line (input/output) and breather connections



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	8196.414 GRM
Custom tariff number	85371010
Country of origin	Malaysia

### Technical data

#### Dimensions

Width	325 mm
Height	300 mm
Depth	121 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Degree of protection	IP66 / NEMA 4X

# Control cabinet - FB-15-SS - 2316190

## Technical data

### General

Mounting position	Vertical
Net weight	4680 g
Housing material	Stainless steel, 316L, electropolished

## Classifications

### eCl@ss

eCl@ss 4.0	27250203
eCl@ss 4.1	27250203
eCl@ss 5.0	27250203
eCl@ss 5.1	27259205
eCl@ss 6.0	27242610
eCl@ss 7.0	27242610
eCl@ss 8.0	27242610

### ETIM

ETIM 3.0	EC001600
ETIM 4.0	EC000261
ETIM 5.0	EC000261

### UNSPSC

UNSPSC 6.01	30211506
UNSPSC 7.0901	39121008
UNSPSC 11	39121008
UNSPSC 12.01	39121008
UNSPSC 13.2	43201553

## Drawings

Dimensioned drawing



