

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



PROFIBUS DP to PROFIBUS PA coupler

Product Description

PROFIBUS head station with a PROFIBUS DP repeater provides network diagnostics and an oscilloscope feature.

Why buy this product

- ☐ One communication interface module can drive up to ten individual PROFIBUS DP or PROFIBUS PA modules
- ✓ Auto detect any baud rate up to 12 Mbps transparently
- Powerful, embedded web server for configuration and access to network diagnostics



Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	600.000 g
Custom tariff number	85176200
Country of origin	Netherlands

Technical data

Ambient conditions

Ambient temperature (operation)	-20 °C 60 °C
Ambient temperature (storage/transport)	-20 °C 60 °C
Degree of protection	IP20

General

Mounting position	On horizontal DIN rail NS 35 in acc. with EN 60715
Net weight	0 g
Color	green
UL, USA/Canada	UL 508 Listed



Technical data

General

UL, Canada	CSA C22.2 No. 142
· ·	

Power supply

Supply voltage range	10.8 V DC 26.4 V DC
Max. current consumption	800 mA
Conductor cross section flexible max.	2.50 mm ²
Conductor cross section flexible min.	0.20 mm ²
Conductor cross section solid max.	2.50 mm ²
Conductor cross section solid min.	0.20 mm ²
Conductor cross section AWG max.	12
Conductor cross section AWG min.	24

Serial interface

Interface 1	Ethernet
Interface	10/100 Mbps Ethernet
Connection method	RJ45
Conductor cross section solid min.	0.2 mm²
Conductor cross section solid max.	2.5 mm²
Conductor cross section flexible min.	0.2 mm²
Conductor cross section flexible max.	2.5 mm²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12

Standards and Regulations

UL, USA/Canada	UL 508 Listed
UL, Canada	CSA C22.2 No. 142

Articles in set

Repeater - FB-DP-RPTR/SC - 2316374



PROFIBUS DP interface/repeater module with oscilloscope functionality



Articles in set

Converter - FB-HSB - 2316379



Head station for monitoring one PROFIBUS network

Classifications

eCl@ss

eCl@ss 5.1	27242208
eCl@ss 6.0	27242208
eCl@ss 8.0	27242608
eCl@ss 9.0	27242608

ETIM

ETIM 5.0	EC001604

Accessories

Accessories

Device coupler

Repeater - FB-DP-RPTR - 2316373



PROFIBUS DP interface/repeater module

Repeater - FB-DP-RPTR/SC - 2316374



PROFIBUS DP interface/repeater module with oscilloscope functionality



Accessories

Repeater - FB-PA/SC - 2316375



PROFIBUS PA interface module with oscilloscope

Converter - FB-HSC - 2316371



Head station for monitoring up to four PROFIBUS networks

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com