



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



CABLE-FCN40/...M/M340

System cables for Telemecanique Modicon® M340

INTERFACE

Data sheet
103912_en_00

© PHOENIX CONTACT - 03/2009



1 Description

These system cables are plugged into Modicon® M340 I/O boards, which are connected via Fujitsu connectors.

Two connection options are available:

CABLE-FCN40/1X50/...M/M340

- Signal transfer of 32 channels

CABLE-FCN40/4X14/...M/M340

- Splitting of 32 channels into 4 x 8 channels

The following I/O boards can be connected:

- BMX DDI 3202K
- BMX DDI 6402K
- BMX DD0 3202K
- BMX DD0 6402K
- BMX DDM 3202K



Make sure you always use the latest documentation.
It can be downloaded at www.phoenixcontact.net/download.



This data sheet is valid for all products listed on the following page:

2 Ordering data

System cables

Description	Cable length	Type	Order No.	Pcs./Pkt.
Assembled round cable , 40-pos. Fujitsu strip on 50-pos. FLK strip (for connecting 32 channels to MODICON® M340 I/O boards)	0.5 m	CABLE-FCN40/1X50/0,5M/M340	2321635	1
	1.0 m	CABLE-FCN40/1X50/1,0M/M340	2321648	1
	2.0 m	CABLE-FCN40/1X50/2,0M/M340	2321651	1
	3.0 m	CABLE-FCN40/1X50/3,0M/M340	2321664	1
	4.0 m	CABLE-FCN40/1X50/4,0M/M340	2321677	1
	6.0 m	CABLE-FCN40/1X50/6,0M/M340	2321680	1
	8.0 m	CABLE-FCN40/1X50/8,0M/M340	2321693	1
	10.0 m	CABLE-FCN40/1X50/10,0M/M340	2321703	1
Assembled round cable , 40-pos. Fujitsu strip on four 14-pos. FLK strips (for connecting 32 channels to MODICON® M340 I/O boards)	0.5 m	CABLE-FCN40/4X14/0,5M/M340	2321716	1
	1.0 m	CABLE-FCN40/4X14/1,0M/M340	2321729	1
	2.0 m	CABLE-FCN40/4X14/2,0M/M340	2321732	1
	3.0 m	CABLE-FCN40/4X14/3,0M/M340	2321745	1
	4.0 m	CABLE-FCN40/4X14/4,0M/M340	2321758	1
	6.0 m	CABLE-FCN40/4X14/6,0M/M340	2321761	1
	8.0 m	CABLE-FCN40/4X14/8,0M/M340	2321774	1
	10.0 m	CABLE-FCN40/4X14/10,0M/M340	2321787	1

3 Technical data

General data	CABLE-FCN40/1X50/.../M340	CABLE-FCN40/4X14/.../M340
Nominal voltage UN	< 50 V AC/60 V DC	
Maximum permissible current carrying capacity per path	1 A	
Maximum conductor resistance	0.16 Ω/m	
Ambient temperature range		
Operation	-20°C ... +50°C	
Storage/transport	-20°C ... +70°C	
Conductor cross-section	0.14 mm ² (26 AWG)	
Conductor structure	7 litz wires, Cu tin-plated	
Outside diameter	10 mm	6.3 mm
Assembly	IDC IEC 60352-4/DIN EN 60352-4	
Connector, control side	40-pos. Fujitsu FCN connection	
Connector, module side	50-pos. flat-ribbon cable connection	4 x 14-pos. flat-ribbon cable connection

4 Color code and pin assignment

CABLE-FCN40/1X50/...M/M340

Connector, control side	Connector, module side	Conductor color
A1	47(-)	Black
B1	37(+)	Brown
A2	35(-)	Red
B2	25(+)	Orange
A3	46	Yellow
B3	45	Green
A4	44	Blue
B4	43	Violet
A5	42	Gray
B5	41	White
A6	40	White-black
B6	39	White-brown
A7	34	White-red
B7	33	White-orange
A8	32	White-yellow
B8	31	White-green
A9	30	White-blue
B9	29	White-violet
A10	28	White-gray
B10	27	Brown-black
A11	23(-)	Brown-red
B11	13(+)	Brown-orange
A12	11(-)	Brown-yellow
B12	1(+)	Brown-green
A13	22	Brown-blue
B13	21	Brown-violet
A14	20	Brown-gray
B14	19	Brown-white
A15	18	Green-black
B15	17	Green-brown
A16	16	Green-red
B16	15	Green-orange
A17	10	Green-blue
B17	9	Green-violet
A18	8	Green-gray
B18	7	Green-white
A19	6	Yellow-black
B19	5	Yellow-brown
A20	4	Yellow-red
B20	3	Yellow-orange

CABLE-FCN40/4X14/...M/M340

	Connector, control side	Connector, module side	Conductor color	
Connection 4 (byte 3)	A1	10(-)	White	
	B1	9(+)	Gray	
	A3	8	Violet	
	B3	7	Blue	
	A4	6	Green	
	B4	5	Yellow	
Connection 3 (byte 2)	A5	4	Orange	
	B5	3	Red	
	A6	2	Brown	
	B6	1	Black	
	Connection 3 (byte 1)	A2	10(-)	White
		B2	9(+)	Gray
A7		8	Violet	
B7		7	Blue	
A8		6	Green	
B8		5	Yellow	
Connection 1 (byte 0)	A9	4	Orange	
	B9	3	Red	
	A10	2	Brown	
	B10	1	Black	
	Connection 3 (byte 1)	A11	10(-)	White
		B11	9(+)	Gray
A13		8	Violet	
B13		7	Blue	
A14		6	Green	
B14		5	Yellow	
Connection 3 (byte 1)	A15	4	Orange	
	B15	3	Red	
	A16	2	Brown	
	B16	1	Black	
	Connection 1 (byte 0)	A12	10(-)	White
		B12	9(+)	Gray
A17		8	Violet	
B17		7	Blue	
A18		6	Green	
B18		5	Yellow	
Connection 1 (byte 0)	A19	4	Orange	
	B19	3	Red	
	A20	2	Brown	
	B20	1	Black	