



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



D-subminiature parallel and serial cables

Ready-to-use cabling – call for custom lengths!**Features**

- Fully molded backshell with strain relief for added protection
- 26 AWG stranded conductors for flexibility
- Thumbscrews for tool-less termination
- All wired straight through except as noted

DB25 to DB25 – All pins terminated

Male to Female	Male to Male	Length	1-9	10-19	20-49	50-99	100+
232AMF5	232AMM5	1.8 m (6 ft)					
232AMF1	232AMM1	3.0 m (10 ft)					
232AMF15	—	4.6 m (15 ft)					
—	232AMM2	7.9 m (26 ft)					
232AMF2	—	7.9 m (26 ft)					

DB9 to DB9 – All pins terminated

Male to Female	Male to Male	Length	1-9	10-19	20-49	50-99	100+
9PAMF6	9PAMM6	1.8 m (6 ft)					
9PAMF10	9PAMM10	3.0 m (10 ft)					
9PAMF15	—	4.6 m (15 ft)					
9PAMF25	9PAMM25	7.9 m (26 ft)					

DB9 to DB25 adapter cable – 15.2 cm (6 in) cable converts 25-pin serial port to a 9-pin AT serial port

DB9 Male to DB25 Female	DB9 Female to DB25 Male	1-9	10-19	20-49	50-99	100+
232CAMR	232CAMS					

DB9 female to DB25 male modem cable – 9-wire, all pins terminated– PC-AT modem Cable

DB25 Male to DB9 Female	Length	1-9	10-19	20-49	50-99	100+
232CAM	1.8 m (6 ft)					
232CAM10	3.0 m (10 ft)					

9-pin null modem cable – Pins 2 and 3 crossed for RS-232 compliance – DB9 connectors on both ends

Female to Female	Male to Female	Length	1-9	10-19	20-49	50-99	100+
232NM9FF6	232NM9MF6	1.8 m (6 ft)					
232NM9	232NM9MF10	3.0 m (10 ft)					
232NM9FF25	232NM9MF25	7.9 m (26 ft)					

Port saver – Protect a highly used port from mechanical damage – Saves you from replacing an expensive card due to port damage

Model No.	Description	1-9	10-19	20-49	50-99	100+
9PSMF	Male to female DB9 port saver					
232PSMF	Male to female DB25 port saver					

USB Cables**High performance USB connectivity and USB extension****Features – USB cables**

- Connect your PC or device to any cable-less USB peripheral
- Type A male to Type B male
- Fully rated USB 2.0 peripheral cables

Features – USB extension cable

- This 3 meter extension cable extends a short cable on a USB peripheral to the full 5 meters length allowed (total cable length must not exceed 5 meters)
- Type A male to type A female



Model No.	Length	1-9	10-19	20-49	50-99	100+
USBAMBM-3F	3 ft (1m)					
USBAMBM-6F	6 ft (2m)					
USBAMBM-15F	15 ft (5m)					

Model No.	Length	1-9	10-19	20-49	50-99	100+
USBAMAF-10F	10 ft (3m)					