



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Model: 232DSP
RS-232 Surge Protector **CE**

Overview

B&B Electronics' Model 232DSP protects RS-232 ports from damage caused by large voltage peaks from lightning and other power problems. The Surge Protector uses 600W Transient Voltage Suppressors to protect pins 2 through 8 and pin 20. It has one DB-25 male and one DB-25 female connector with all 25 pins passing straight through. The TVSs are connected between the ground screw and pins 2,3,4,5,6,7,8, and 20. The 232DSP will suppress any voltage levels above 12 volts without affecting the normal RS-232 data.

The 232DSP is placed inline, between the data cable and the RS-232 port, as close to the protected port as possible. The ground screw must be connected to earth ground. A minimum of 12 AWG copper wire is recommended. B&B's Model CU15B is 1.5 x 0.016 in (38 x .25 mm) copper cut to length for ground connections that are longer than a few feet (one meter). If this device is not properly grounded it will not protect RS-232 lines.

Specifications

Clamping Voltage: 12 volts
Peak Pulse Power: 600 watts @ 1 msec.
Response Time: less than 1 picosecond
Typical Capacitance: 200 picofarads
Ground Screw: size 10#

DECLARATION OF CONFORMITY

Manufacturer's Name: B&B Electronics Manufacturing Company
Manufacturer's Address: P.O. Box 1040
707 Dayton Road
Ottawa, IL 61350 USA
Model Number: 232DSP
Description: RS-232 Surge Protector
Type: Light industrial ITE equipment
Application of Council Directive: 89/336/EEC
Standards: EN 50082-1
EN 61000 (-4-2, -4-3, -4-4, -4-6)

Robert M. Paratore, Director of Engineering



DB25M Model 232DSP DB25F

