



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Model: 232MDS3
Modem Data Splitter



Overview

The Modem Data Splitter can be connected so that three computers or terminals can use one modem without manual switching. The Modem Data Splitter can be used to combine three DTE ports to a DCE port.

All signals entering the female DTE connectors on pin 2 (Transmit Data), 4 (Request To Send), and 20 (Data Terminal Ready) are diode OR'd together and appear as outputs on the male DCE connector. Pins 3 (Receive Data), 5 (Clear To Send), 6 (Data Set Ready), and 8 (Carrier Detect) are normally outputs from a DCE port, so they are connected directly from the male to all female connectors. Can be left permanently installed.

To ensure proper operation, lines 2, 4, and 20 on the unused female inputs should be low or open to allow the other inputs to operate properly. Pins 1 and 7 are connected to provide a ground path. Pin 1 is Protective Ground and Pin 7 is Signal Ground on all three DB25 connectors.

To install the 232MDS3, connect a "straight through" cable (Pin 1 to Pin 1, Pin 2 to Pin 2, etc.) between the MDS and the modem. Any pin reversing or jumpering should be done on the cables that connect to the computers or terminals.

DECLARATION OF CONFORMITY

Manufacturer's Name:	B&B Electronics Manufacturing Company
Manufacturer's Address:	P.O. Box 1040 707 Dayton Road Ottawa, IL 61350 USA
Model Number:	232MDS3
Description:	Modem Data Splitter
Type:	Light industrial ITE equipment
Application of Council Directive:	89/336/EEC
Standards:	EN 50082-1 EN 61000 (-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11)

Robert M. Paratore, Director of Engineering

