

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Retractable vacuum seal nozzle

Seal heat timer

Seal cool timer

Pneumatic jaw 1/8" heat seal

Pneumatic pressure jaw

Foot switch activated. Controls vacuum time.

The SCS Vacuum Sealer removes moisture laden air from the interior of moisture barrier bags, and heat seals the bags closed. This is part of the dry packaging process that protects surface mount devices from moisture. A vacuum sealer, a moisture barrier bag, desiccant, and humidity indicator card (HIC) are needed for dry packaging.

The SCS Vacuum Sealer is available with or without a ¼" seal bar. A retractable nozzle is used to improve bag evacuation and save bag space. The operator controls vacuum time by using the foot pedal. Timers are provided for heat sealing and cooling. By placing the heat seal jaw close to the top of the bag, the amount of bag used in the sealing process is reduced.

Specifications	Typical Value
Seal Length	20"
Seal Width	1/8"
Vacuum Pressure	< 26 Hg
Max Suction	0.8 CFM
Air Consumption	1.75 CFM
Length	25.5"
Width	10"
Height	9"
Electrical Power	120 VAC
Compressed Air	80 PSI

Item	Description
235VACUSEAL	20"
235VACUSEAL-1/4	20" with 1/4" seal bar

235VACUSEAL VACUUM SEALER

SCS

926 JR Industrial Drive, Sanford, NC 27332

WEB SITE: StaticControl.com PHONE (919) 718-0000 DRAWING NUMBER 235VACUSEAL May 2016