



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



System 273

23711RB

Old item no.: 23711RB



SYSTEM 273RB-RLI

23mm Binocular Stereo-Zoom Microscope with sturdy, heavy-duty, cast aluminum housing and dual boom ball-bearing boomstand. Nearly 8in. working distance (when used with a 0.5X reducing lens), 7X-45X magnification range and 0.7X-4.5X zoom range. 150W Fiber Optic Illuminator with continuous annular ring light included.



Electrical data

Maximum frequency (Hz)	6 0
Minimum frequency (Hz)	5 0
Maximum voltage (V)	1 2 0
Voltage from (V)	1 0 0
Total consumption (W)	1 5 0

Dimensions

Net weight (kg)	0
Arm length (in.)	2 6
Gross weight (lb.)	6 5

Body

Body color	Grey
Body material	Aluminum

Lightsource

Number of lamps	1
Lamp base	GX5.3
Lightsource	MR16
CRI and/or Color Temperature	3000K

Optic

Material of diffuser	Glass
Working distance (mm)	1 1 8

Termination

Cord length (ft)	5
Mounting	Boomstand

Technical data

IP classification	2 0
-------------------	-----