



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Communication module - NLC-COM-CELLULAR-CDMA - 2400428

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



CDMA communication module. Allows SMS messaging to and from the Nanoline controller when connected to the Verizon network.

Product description

Adds CDMA connectivity to Nanoline controller, allowing SMS messaging. Attaches to left-side of base unit.

Product Features

- Allows access to read and write registers, flags, timers, and counters
- Sends system faults and warning messages
- Password protection for selective access or broadcast to an onboard address book
- Switches outputs on and off
- Reads inputs
-



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	240.0 GRM
Custom tariff number	85176200
Country of origin	India

Technical data

Dimensions

Width	80.5 mm
Height	103.5 mm
Depth	43 mm

Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C

Communication module - NLC-COM-CELLULAR-CDMA - 2400428

Technical data

Ambient conditions

Permissible humidity (operation)	90 %
Degree of protection	IP20

Wireless interface

Designation	CDMA
Wireless standard	CDMA-SMS
Antenna connection method	SMA (female)
Frequency band	800/1900 MHz

Power supply for module electronics

Connection method	Screw connection
Supply voltage range	12 V DC ... 24 V DC (9.6 ...28.8 V DC)

General

Net weight	152 g
------------	-------

Classifications

eCl@ss

eCl@ss 4.0	27250315
eCl@ss 4.1	27250315
eCl@ss 5.0	27242216
eCl@ss 5.1	27242216
eCl@ss 6.0	27242216
eCl@ss 7.0	27242216
eCl@ss 8.0	27242216

ETIM

ETIM 2.0	EC001417
ETIM 3.0	EC001417
ETIM 4.0	EC001417
ETIM 5.0	EC001417

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Communication module - NLC-COM-CELLULAR-CDMA - 2400428

Drawings

Dimensional drawing

